

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

REVISED FILING

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

502 V & J Tower - Midland, Texas  
(Place)

October 17, 1960  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the SAMEDAN OIL CORPORATION

DeBorde

(Company or Operator)

Well No. 1 in N

(Unit)

SE  $\frac{1}{4}$  SW  $\frac{1}{4}$  of Sec. 15, T. 11S, R. 31E, NMPM., Wildcat (Undes) Pool

(40-acre Subdivision)

Chaves

County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

DeBorde Well No. 1 was drilled to 10,955 feet in lime without encountering Commercial Production of oil or gas and was abandoned at this depth. Intermediate 8 5/8" casing was set at 3620 feet. We propose to plug and abandon the location by loading 7 7/8" open hole with 50 viscosity drilling mud and spotting cement plugs to isolate all porosity intervals. Plugs are to be set as follows: 35 sacks cement 10,955 to 10,777, 25 sacks 8528 to 8438, 25 sacks 6327 to 6237, 25 sacks 4829 to 4739, 25 sacks 3650 to 3580. Cement will be some 40 feet up in the intermediate casing that is set at 3620'. We will erect a 4" X 4' marker at the surface with legal description of well. Verbal approval to P & A this well was obtained 10-7-60.

In the event the intermediate casing can be salvaged, we will notify the O.C.C. as to plug depths above casing cut off point. If we are not able to salvage any intermediate casing we will spot a 15 sack cement plug from 0 to 44' in the 8 5/8" casing.

Approved \_\_\_\_\_, 19\_\_\_\_  
Except as follows:

Approved \_\_\_\_\_  
OIL CONSERVATION COMMISSION

By \_\_\_\_\_

Title \_\_\_\_\_

SAMEDAN OIL CORPORATION  
Company or Operator

By \_\_\_\_\_

Position ENGINEER

Send Communications regarding well to:

Name SAMEDAN OIL CORPORATION

Address 502 V & J Tower - Midland, Texas