

## NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

**MISCELLANEOUS NOTICES**

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
		NOTICE OF INTENTION TO PLUG WELL	<b>X</b>

This file brought over from Artesia  
by Mr. Hanson

Artesia, New Mexico  
Place

March 1, 1948  
Date

Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Henry & Co. Lea State Well No. 1 in SW 1/4  
Company or Operator Lease  
of Sec. 26, T. 11, R. 31, N. M. P. M., Wildcat Field.  
Chaves County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

The above well was drilled to 1225' in lime sulfur water encountered 1220'. 2000' water in hole.

Permission is requested to plug and abandon well as follows: Set cement plug from 1150' to total depth to shut off water. Fill hole with mud to 2250'. Set cement plug 2200'-2250'. Set cement plug at base 8 5/8" csg. Pull 8 5/8" and set cement plug at top of 8 5/8". Fill hole with heavy mud to 50' and set cement plug to surface with marker.

## WELL INFORMATION

Total depth-1225'. Encountered sulfur water 1220'. 8 5/8" casing set @ 1640' with 75 Sex. 7" casing hung in hole @ 3520 to prevent "Red Sand" from caving in. Top Anhydrite 1150'. Top Salt 1585'. Base Salt 2205'. Top Red Sand 2955'.. Top Lime 3185'.

Approved \_\_\_\_\_, 19\_\_\_\_  
except as follows:

Henry & Co.  
Company or Operator  
By (Signed) Harry B. Williams

Position Agent  
Send communications regarding well to  
Henry & Co.

Name \_\_\_\_\_  
Address 503 Esperson Building

Houston, Texas

OIL CONSERVATION COMMISSION,

By \_\_\_\_\_

Title \_\_\_\_\_



## NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

**MISCELLANEOUS NOTICES**

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	X
NOTICE OF INTENTION TO DEEPEN WELL			

Artesia, New Mexico  
PlaceMarch 1, 1948  
Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Henry & Co. Les State Well No. 1 in SW SE  
Company or Operator Lease  
of Sec. 26, T. 11, R. 31, N. M. P. M., Wilcox Field  
Chaves County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

The above well was drilled to 1285' in lime sulfur water encountered 1220'. 2000' water in hole.

Permission is requested to plug and abandon well as follows: Set cement plug from 1150' to total depth to shut off water. Fill hole with mud to 2250'. Set cement plug 2200'-2250'. Set cement plug at base 8 5/8" seg. Pull 8 5/8" and set cement plug at top of 8 5/8". Fill hole with heavy mud to 50' and set cement plug to surface with marker.

## WELL INFORMATION

Total depth - 1285. Encountered sulfur water 1220. 8 5/8" casing set @ 1610 with 75 Sax. 7" casing swung in hole @ 3520 to prevent "Red Sand" from coming in. Top Anhydrite 1150. Top Salt 1505. Base Salt 2205. Top Red Sand 2955. Top Lime 3135.

Approved \_\_\_\_\_, 19\_\_\_\_  
except as follows:

Henry &amp; Co.

Company or Operator

By Harry B. Williams *rx*Position Agent

Send communications regarding well to

Name Henry & Co.Address 505 Esperson BuildingHouston, Texas

OIL CONSERVATION COMMISSION,

By \_\_\_\_\_

Title \_\_\_\_\_

