## Photos CAT

-NEW MEXICO OIL CONSERVATION COMPISSION

Santa Fe, New Mexico

## NOTICE OF INTENTION TO DRILL



Notice must be given to the Oil Conservation Commission or its proper agent and approval plained being distinct begins. If changes in the proposed plan are considered advisable, a copy of this notice showing states win returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See a copy of the commission.

	~~~~~~~~	<u>Ar</u>	tesia, Ney	Mexico	August 1	3, 1947
		OMMISSION,	- Fiat		_	· Date
ita Fe, Nei	w mexico,					
ntlemen:	are hereby	notified that it is an	m intention to com	manaa tha drii	lling of a wall to be l	ZDOWN 98
					lling of a well to be l	
· <b>)</b>	Compa	ny or Operator	State A	Lease	Well No	IN NWNE
Sec. 11	, T	13 , R 31	, N. M., P. M.,C	aprock-	Field, Chave	Coun
	N			•	ne North line ar	
		∰ (W.) o	f the <b>Fast</b>	line of	otion 11	
	0	(Give l	ocation from secti	on or other le	gal subdivision lines.	Cross out wro
		•	the oil and gas le	ase is No.	399 Assignment	No
		Address				
iii		lf governme	ent land the permi	ittee is		
		Address				
		The lessee is		7		
ABEA 6	40 ACRES					
CATE WEI	LL CORRECT	LY We propose	to drill well with d	rilling equipme	ent as follows:Rot	ary tools
nmission i	f a bond fo s as follows	or this well in conf	nket Bond o	n File w	General Rules and F 1th Comm1 s s 10 as indicated:	-
mmission i	f a bond fo s as follows	or this well in conf :::\$10,000-Bla	ormance with Ru	n File w	ith Commissio	-
mmission is propose to	f a bond for a sas follows to use the fol	or this well in conf :: \$10,000 Bla lowing strings of cas	ormance with Ruinket Bond or ing and to land or	n File w	as indicated:	Sacks
mmission is propose to	f a bond for a follows or use the follows Casing	or this well in conf 10,000 Bla llowing strings of cas Weight Per Feet	ormance with Ruinet Bond or ing and to land or New or Second Hand	cement them	as indicated:  Landed or Cemented	Sacks Coment
Size of Hole  112  8 1/4  changes in first production	f a bond for a sas follows to use the follows the follows of Casing 9 5/8	or this well in conformal well of the second well o	ormance with Ruinket Bond or ing and to land or Second Hand S.H.  New we will notify you	cement them  Depth  250  3015	as indicated:  Landed or Cemented  Cemented  Cemented  Cemented	Sacks Coment 150 600
Bize of Hole  112  8 1/4  changes in a first productional info	f a bond for a sar follows to use the follows the follows of Casing 9 5/8 7 11  the above placetive oil of formation:	weight Per Feet  Weight Per Feet  22  an become advisable r gas sand should oc	nket Bond or ing and to land or Second Hand  New  New  we will notify you car at a depth of	n File we cement them  Depth 250 3015  before cement about 303	as indicated:  Landed or Cemented  Cemented  Cemented  Cemented	Sacks Cornent 150 600
Bize of Hole  112  8 1/4  changes in e first productional info	f a bond for a safellows of use the follows of the casing 9 5/8 7 # the above placetive oil or formation:	or this well in conformation of the well o	nket Bond or ing and to land or Second Hand  New  New  we will notify you car at a depth of	cement them  Depth  250  3015	as indicated:  Landed or Cemented  Cemented  Cemented  Cemented	Sacks Coment 150 600
Bize of Hole  112  8 1/4  changes in e first productional info	f a bond for a sar follows to use the follows the follows of Casing 9 5/8 7 11  the above placetive oil of formation:	weight Per Feet  Weight Per Feet  22  an become advisable r gas sand should oc	nket Bond or ing and to land or Second Hand  New  New  we will notify you car at a depth of	n File we cement them  Depth 250 3015  before cement about 303	as indicated:  Landed or Cemented  Cemented  Cemented  Cemented	Sacks Coment 150 600
Bize of Hole  112  8 1/4  changes in first productional info	f a bond for a safellows of use the follows of the casing 9 5/8 7 # the above placetive oil or formation:	weight Per Feet  Weight Per Feet  22  an become advisable r gas sand should oc	New or Second Hand  New or Second Hand  New or Second Hand  S.H.  New  we will notify you car at a depth of	n File we cement them  Depth 250 3015  before cement about 303	as indicated:  Landed or Cemented  Cemented  Cemented  ting or landing casing.  feet.	Sacks Coment 150 600
Bize of Hole  112  8 1/4  changes in e first productional info	f a bond for a safellows of use the follows of the casing 9 5/8 7 # the above placetive oil or formation:	weight Per Feet  Weight Per Feet  22  an become advisable r gas sand should oc	New or Second Hand  New or Second Hand  New or Second Hand  S.H.  New  We will notify you car at a depth of	Depth 250 3015 before cement about 303 rely yours, Habay	Landed or Cemented  Cemented  Cemented  ting or landing casing.  feet.	Sacks Coment  150 600  We estimate the
mmission is propose to size of Hole  112  8 1/4  changes in a first productional information informati	f a bond for a sar follows to use the follows:  9 5/8  7 11  the above pluctive oil or formation:	weight Per Feet  Weight Per Feet  22  an become advisable r gas sand should oc	ing and to land or  New or Second Hand  S.H.  New  we will notify you cur at a depth of  By  Positi	Depth 250 3015 before cement about 303 rely yours, Manry on H.B. W	as indicated:  Landed or Cemented  Cemented  Cemented  ting or landing casing.  feet.	Sacks Coment  150 600  We estimate th
mmission in proved except as	f a bond for a sar follows to use the follows:  9 5/8  7 11  the above pluctive oil or formation:	Weight Per Feet  40 22  an become advisable r gas sand should oc	ing and to land or  New or Second Hand  S.H.  New  we will notify you cur at a depth of  By  Positi Send	cement them  Depth  250  3015  before cement about 303  rely yours,  Manry  on H.B. W	Landed or Cemented  Cemented  Cemented  Cemented  ting or landing casing.  feet.	Sacks Coment  150 600  We estimate the
Size of Hole  112  8 1/4  changes in e first productional info	f a bond for a sar follows to use the follows:  9 5/8  7 11  the above pluctive oil or formation:	Weight Per Feet  40 22  an become advisable r gas sand should oc	ing and to land or  New or Second Hand  S.H.  New  we will notify you cur at a depth of  By  Positi	cement them  Depth  250  3015  before cement about 303  rely yours,  Manry  on H.B. W	Landed or Cemented  Cemented  Cemented  Cemented  ting or landing casing.  feet.	Sacks Coment  150 600  We estimate the

A property of the second of th