

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.15. LEASE DESIGNATION AND SERIAL NO.
LC - 069832 A

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER Water Injection	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
2. NAME OF OPERATOR Union Oil Company of California	7. UNIT AGREEMENT NAME
3. ADDRESS OF OPERATOR P. O. Box 671, Midland, Texas 79701	8. FARM OR LEASE NAME Tract 9 Caprock Queen Unit, S.
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNL and 660' FEL of Sec. 5.	9. WELL NO. I
14. PERMIT NO.	10. FIELD AND POOL OR WILDCAT Caprock Queen (Chaves)
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4429' GR	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 5, 15-S, 31-E.
	12. COUNTY OR PARISH Chaves
	13. STATE N. Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☒	FRACTURE TREATMENT ☐	ALTERING CASING ☒
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-8-68

Pumped plug #1 75 ex. cement down 5 1/2" casing. Installed wiper plug and pumped 25 ex. cement - WOC 12 hours and tested to 1000 psi for 30 min. OK - shot off casing at 1218' and recovered 1221'. Set cement plugs as follows:

#2 - 40 ex. cement - 1252' to 1084'
#3 - 50 ex. cement - 353' to 161'
#4 - 10 ex. cement - 20' to 0'.

Installed dry hole marker. Plugging complete 9-10-68. Left 273' of 8 5/8" OD casing in hole and 1985' of 5 1/2" OD casing.

RECEIVED
SEP 30 1968
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct.

SIGNED

John R. Gray

Drilling Superintendent

Sept. 17, 1968

TITLE

DATE

(This space for Federal or State use)

APPROVED BY
COMPLETION OF APPROVAL, IF ANY:

TITLE

RECEIVED

JUL 11 1969

H. L. BECKMAN

ACTING DIRECTOR

*See Instructions on Reverse Side

JUL 14 1969

O. C. C.
ARTESIA, OFFICE

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.