


Form 9-331a
(Feb. 1951)

(SUBMIT IN TRIPLICATE)

Land Office

Lease No.



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

600

X

MAR 16 PM 3:00

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		March 16 55
Federal-Mexican		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

1-17

660

660

3/4 of section 17, T-15-S R-31-E N.M.P.M., 19

Unidentified is located ~~2000~~ ft. from $\left\{ \begin{matrix} N \\ S \end{matrix} \right\}$ line and ~~New Mexico~~ $\left\{ \begin{matrix} E \\ W \end{matrix} \right\}$ line of sec.
Unknown at present

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is ft.

Drill 11" hole to approximately 300' and cement 8-5/8" casing with 200 sz.

DETAILS OF WORK

Drill 7-7/8" hole to approximately 3000' and cement 3-1/2" casing; indicate mudding jobs, cementing points, and all other important proposed work.

Core the Queen sand to check possible production. If production is indicated, cement 5 1/2" casing at 3100' with enough cement to cover the salt section.

Union Oil Company of California

619 West Texas Avenue

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Midland, Texas Ass't Division Engineer

Address

By James E. Poyon

Title