

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach to this

TOOLS USED

Rotary tools were used from 0 feet to 3181 feet, and from feet to feet
 Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to Producing 6/6, 1955

OIL WELL: The production during the first 24 hours was 174 barrels of liquid of which 100% was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity 38

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy	1374		T. Devonian		T. Ojo Alamo
T. Salt	1395		T. Silurian		T. Kirtland-Fruitland
B. Salt	2285		T. Montoya		T. Farmington
T. Yates	2327		T. Simpson		T. Pictured Cliffs
T. 7 Rivers			T. McKee		T. Menace
T. Queen	3138		T. Ellenburger		T. Point Lookout
T. Grayburg			T. Gr. Wash		T. Mancos
T. San Andres			T. Granite		T. Dakota
T. Glorieta			T.		T. Morrison
T. Drinkard			T.		T. Penn
T. Tubbs			T.		T.
T. Abo			T.		T.
T. Penn			T.		T.
T. Miss			T.		T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	235	335	Surface				
335	1000	665	Red bed				
1000	1535	535	Red bed & anhy				
1535	1820	285	Anhy				
1820	2212	392	Anhy & red bed				
2212	2596	384	Anhy & gyp				
2596	2664	68	Anhy & lime				
2664	2890	226	Lime & sand				
2890	3009	119	Lime & anhy				
3009	3090	81	Lime				
3090	3181	91	Anhy & sand, lime				