

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

Company or Operator

Address

Well No.

In

of Sec.

T

Cooperative Producing Ass'n Box # 978, Lovelland, Texas

Livermore Ohio State

2

Field

NE/SE

11

135

County.

Well is feet south of the North line and feet west of the East line of

If State and the oil and gas lease is No. Caprock Assignment No. Chaves

If patented 660 and the owner is 1900 Address Sec. 11-T135-R31E.

If Government land the permittee is Address

The Lessee is Address

Drilling commenced 19 Drilling was completed 19

Name of drilling Cooperative Producing Ass'n Address Lovelland, Texas

Elevation above sea level at 4-15-48 feet. 5 - 10 - 48

The information given is to be used by Gen. P. Livermore, Inc. Lubbock, Texas

## SANDS OR ZONES

No. 1, from to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from 3022' to 3040' No. 6, from to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

## CASING RECORD

| SIZE | WEIGHT PER FOOT | THREADS PER INCH | MAKE | AMOUNT | KIND OF SHOE | CUT & FILLED FROM | PERFORATED |    | PURPOSE |
|------|-----------------|------------------|------|--------|--------------|-------------------|------------|----|---------|
|      |                 |                  |      |        |              |                   | FROM       | TO |         |
| 95/8 | --              | 10               | Used | 320'   | Baker        |                   |            |    | None    |
| 7"   | 20              | 10               | Used | 3017'  | Baker        |                   |            |    | None    |
|      |                 |                  |      |        |              |                   |            |    |         |
|      |                 |                  |      |        |              |                   |            |    |         |
|      |                 |                  |      |        |              |                   |            |    |         |

## MUDDING AND CEMENTING RECORD

| SIZE OF HOLE | SIZE OF CASING | WHERE SET | NO. SACKS OF CEMENT | METHOD USED | MUD GRAVITY | AMOUNT OF MUD USED |
|--------------|----------------|-----------|---------------------|-------------|-------------|--------------------|
|              |                |           |                     |             |             |                    |
|              |                |           |                     |             |             |                    |
|              |                |           |                     |             |             |                    |
| 12 1/2       | 95/8           | 320'      | 150                 | Halliburton |             |                    |
| 8 3/4        | 7"             | 3017'     | 600                 | Halliburton |             |                    |

## PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

| SIZE | SHELL USED | EXPLOSIVE OR CHEMICAL USED | QUANTITY | DATE    | DEPTH SHOT OR TREATED | DEPTH CLEANED OUT |
|------|------------|----------------------------|----------|---------|-----------------------|-------------------|
|      |            |                            |          |         |                       |                   |
|      |            |                            |          |         |                       |                   |
| 5"   | 50"        | Nitro-Gly.                 | 50 qts.  | 5-10-48 | 3033-3046             | 3046              |

Results of shooting or chemical treatment

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from Surface feet to 3019' feet, and from feet to feet

Cable tools were used from 3017' feet to 3046 feet, and from feet to feet

## PRODUCTION

Put to producing 5- 23- 19 48

The production of the first 24 hours was 66 barrels of fluid of which 99.6 % was oil; .4 %

emulsion; -0- % water; and % sediment. Gravity, Be 36.4

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

## EMPLOYEES

Paul Holloway, Supt. Driller Driller

Driller Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 4th Lovelland, Texas 6-4-48

day of June 19 48 Name

Lola Watson Notary Public Gen. Mgr.

Haskell County, Texas

## FORMATION RECORD

| FROM | TO   | THICKNESS<br>IN FEET | FORMATION                |
|------|------|----------------------|--------------------------|
| -0-  | 320  | 320                  | Surface                  |
| 320  | 931  | 611                  | Red Bed                  |
| 931  | 1443 | 512                  | Red Bed & Shale          |
| 1443 | 1560 | 117                  | Red Bed                  |
| 1560 | 1657 | 97                   | Salt                     |
| 1657 | 1720 | 63                   | Salt & Shale             |
| 1720 | 1852 | 132                  | Anhydrite & Shale        |
| 1852 | 2226 | 374                  | Salt, Anhydrite & Shells |
| 2226 | 2400 | 174                  | Anhydrite & Shale        |
| 2400 | 2435 | 35                   | Anhydrite & Sand         |
| 2435 | 2482 | 47                   | Anhydrite & Shells       |
| 2482 | 2572 | 90                   | Anhydrite                |
| 2572 | 2660 | 88                   | Anhydrite & Shale        |
| 2660 | 2747 | 87                   | Anhydrite & Shells       |
| 2747 | 3028 | 281                  | Anhydrite                |
|      |      | 3028                 | Total Depth              |