

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
E-5758

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	MAR 24 1970	7. Unit Agreement Name
2. Name of Operator	Great Western Drilling Company	Central Caprock Queen 13
3. Address of Operator	P. O. Box 1659 Midland, Texas 79701	8. Farm or Lease Name
4. Location of Well	UNIT LETTER M, 330 FEET FROM THE West LINE AND 660 FEET FROM THE South LINE, SECTION 13 TOWNSHIP 13-S RANGE 31-E NMPM.	9. Well No.
		13
		10. Field and Pool, or Wildcat
		Caprock Queen
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
	4405 T/Tbg. Head	Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-1/2" casing is set at 3095' and perforated from 3060' to 3068'. We propose setting a 25 sack cement plug at 3060'. An estimated 1200' of 5-1/2" casing will be pulled and a 25 sack plug will be placed at the casing stub. A 25 sack plug will be placed in the bottom of the 8-5/8" surface casing at 218' and a 10 sack plug will be placed at the surface. Mud-laden fluid will be placed between the plugs.

Tract 18 Formerly the Ada Oil Co. Gulf State No. 1-13

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>R. I. Comstock</u>	TITLE <u>Chief Engineer</u>	DATE <u>MAR 23 1970</u>
APPROVED BY <u>[Signature]</u>	TITLE <u></u>	DATE <u></u>
CONDITIONS OF APPROVAL, IF ANY:		