AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

ind Day

il room Tid signi

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Consequence of Emmission, Santa Fo. New Mexico, or its proper agent not more than twelfy days after completion of well. Follow instructions in the Rules and Regulation of the Commission, Indicate questionable data by following the with (?). SUBMIT IN TRIPLICATE, FORM C-110 WILL NOT BE APPROVED UNTIFORM C-105 IS PROPERLY TRILED OUT.

Barney Ceckburn _Well No. _, N. M. P. M., Caprock 31E County. Well is 1980 feet south of the North line and 1980 of the line of Sec. 13-138-31E If State land the oil and gas lease is No. 1-10424 Assignment No. _____ Address_ If patented land the owner is... If Government land the permittee is... The Lessee is Barney Coakburn & C. V. Cartie , Address Artesia, New Mexico 19.47 Drilling was completed Drilling commenced May 6. Name of drilling contractor Barney Cockburn , Address Artesia, N. M. Elevation above sea level at top of casing _____feet. The information given is to be kept confidential until OIL SANDS OR ZONES 3060 No. 1. from ____ No. 4, from___ No. 6. from... No. 3; from_ IMPORTANT WATER SANDS Include data on rate of water inflow and elevation to which water rose in hole. No. 2. from.... CASING RECORD CUT & FILLED FROM PERFORATED PURPOSE AMOUNT MAKE 8 5/8 236 5 1/2 3032 30041 MUDDING AND CEMENTING RECORD NO. SACKS OF CEMENT SIZE OF CASING METHOD USED MUD GRAVITY AMOUNT OF MUD USED WHERE SET 2551 5/8 50 Halliburten 500 PLUGS AND ADAPTERS ____Depth Set___ Heaving plug-Material __Length_ __Size____ Adapters-Material RECORD OF SHOOTING OR CHEMICAL TREATMENT EXPLOSIVE OR CHEMICAL USED QUANTITY DATE . DEPTH CLEANED OUT SIZE SHELL USED 3060-3068 4" Nitro-glycerin 20 qts 10-6-47 3068 Results of shooting or chemical treatment. Well tested 36 bbls. eil en 24 heur test. FUMPING RECORD OF DRILL-STEM AND SPECIAL TESTS If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto. TOOLS USED Rotary tools were used from 0 feet to 3039 feet, and from feet to feet Cable tools were used from 3039 feet to 3068 feet, and from feet to feet **PRODUCTION** Put to producing Oct. 15, 19 47 The production of the first 24 hours was emulsion; ______% water; and ______% sediment. Gravity, Be____ Gallons gasoline per 1,000 cu. ft. of gas_____ If gas well, cu, ft. per 24 hours Rock pressure, lbs. per sq. in.__ **EMPLOYEES** _____, Driller _____ N. C. West C. N. N1118 ______, Driller ________, Driller _______, Driller Wayne Adkins FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all

Subscribed and sworn to before me this 22nd

work done on it so far as can be determined from available records.

Artesia, New Mexico Oct. 22,]

FROM	TO	THICKNESS IN FEET	FORMATION	
0 310 1300 1376 1469 1561 1950 2140 2275 2375 2500 2600 2630 2630 2805 2945 3039	310 1300 1376 1469 1561 1950 2140 2275 2375 2800 2800 2800 2805	310 990 76 93 92 389 190 135 100	Sand & Gravel Red Bed Shale Slate & Anhydrite Anhydrite Salt Salt & Shale Anhydrite, Shale & Salt Anhydrite Anhydrite Anhydrite Anhydrite & Red Bed Anhydrite & Red Bock Anhydrite Anhydrite Anhydrite Anhydrite Anhydrite Anhydrite Anhydrite	
3052 30 57	3057 3068 TD	5	Lime & Shells	
		4		
	7% , \$279			
·. ·				
		. D		
			The first of the second of th	
	- :		1964 6	
	a the second was		The second of th	•
\$ * - *				
			ALL THE STATE OF T	-
		5		
				
#				
	€ To Stand Medical Standard			
		11 CM 11 1.7	A STATE OF TOPAN TO COMPANY TO STATE OF THE	
		; ·		
		- tage - 10		
		100 mg (100 mg)	The state of the s	