

AREA 640 ACRES  
LOCATE WELL CORRECTLY

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

1955 MAR 18 PM 1:21  
WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

White-Geror Oil Corp.

(Company or Operator)

State

(Lease)

Well No. 5, in NE  $\frac{1}{4}$  of SE  $\frac{1}{4}$  of Sec. 22, T. 13S, R. 31E, NMPM.Drickey-QueenPool, Chaves

County.

Well is 1980 feet from South line and 660 feet from East lineof Section 22. If State Land the Oil and Gas Lease No. is ?Drilling Commenced 2-3, 1955 Drilling was Completed 2-25 1955Name of Drilling Contractor Southwestern Drilling CompanyAddress Lovington, New MexicoElevation above sea level at Top of Tubing Head DE 4434 The information given is to be kept confidential until  
No, 19    

## OIL SANDS OR ZONES

No. 1, from 3038 to 3050 No. 4, from      to     No. 2, from      to      No. 5, from      to     No. 3, from      to      No. 6, from      to     

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 125' to 155' feet.No. 2, from      to      feet.No. 3, from      to      feet.No. 4, from      to      feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8 5/8"		X	164'				Water shut off
5 1/2"		X	3038				Oil String

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	8 5/8"	164	100			
	5 1/2"	3038	100			

## RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Sand oil frac open hole from 3038-3055

(10,000 gal. oil plus 7500 lbs. Sd. plus 200 Bbl oil Flush)

Result of Production Stimulation 1 PP 528 BOPD (Based on 66 BO in 3 hrs. after load)Depth Cleaned Out 3055

LOG OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 3038 feet, and from 3038 feet to 3055 feet.  
Cable tools were used from 3038 feet to 3055 feet, and from 3055 feet to 3055 feet.

PRODUCTION

Put to Producing 2-25, 1955

OIL WELL: The production during the first 24 hours was 528 barrels of liquid of which 100% was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity 37

GAS WELL: The production during the first 24 hours was TSTM M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy.	1450	T. Devonian	T. Ojo Alamo
T. Salt	1510	T. Silurian	T. Kirtland-Fruitland
B. Salt	2130	T. Montoya	T. Farmington
T. Yates	2285	T. Simpson	T. Pictured Cliffs
T. 7 Rivers		T. McKee	T. Menefee
T. Queen	3038	T. Ellenburger	T. Point Lookout
T. Grayburg		T. Gr. Wash	T. Mancos
T. San Andres		T. Granite	T. Dakota
T. Glorieta		T.	T. Morrison
T. Drinkard		T.	T. Penn
T. Tubbs		T.	T.
T. Abo		T.	T.
T. Penn		T.	T.
T. Miss		T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	125	125	Caliche				
125	155	30	Water Sand				
155	1450	1295	Red Shale				
1450	1510	60	Anhy.				
1510	2130	620	Salt				
2130	2285	155	Anhy. & Red Sh.				
2285	2400	115	Yates, Red Sd.				
2400	3038	638	Red Sh, Salt & some Red Sd.				
3038	3050	12	Grey Sd. w/oil St.				
3050	3055	5	Anhy.				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Chas. D. Sands 18-55

(Date)

Company or Operator White-Geror Oil Corp.

Address

Name

Position or Title

Geologist

C. D. SANDS  
303 Green Acres  
Hobbs, New Mexico