### INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 26 days after the completion of any newly-arilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate exception state land, where six copies are required. See Rule 1105.

#### INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

## Southeastern New Mexico

### Northwestern New Mexico

1//01			
T. Anhy <u>1440'</u>	T. Canyon	T. Ojo Alamo	T. Penn. ''B''
T. Salt1550.'	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt2120'	T. Atoka	T. Pictured Cliffs	T. Penn. ''D''
T. Yates 2275 *	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen <u>3029'</u>	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	_ T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Qtzte
T. Glorieta	Т. МсКее	Base Greenhorn	T. Granite
T. Paddock	_ T. Ellenburger	T. Dakota	T
T. Blinebry	T. Gr. Wash	T. Morrison	T
T. Tubb	T. Granite	T. Todilto	T
T. Drinkard	T. Delaware Sand	T. Entrada	T
T. Abo	T. Bone Springs	T. Wingate	T
T. Wolfcamp	T	T. Chinle	T
T. Penn	T	T. Permian	T
T Cisco (Bough C)	T		T

# FORMATION RECORD (Attach additional sheets if necessary)

From	То	Thickness in Feet	Formation _	From	То	Thickness in Feet	Formation
0	125	125	Caliche				
125	155	30	Water sand				
155	1440	1285	Red shale				
1440	1500	60	Anhy.				
1500	2120	620	Salt		ł		
2120	2275	155	Anhy. & Red shale				
2275	2390	115	Red sand (Yates)				
2390	3029	639	Red shale,salt,anhy.&reds				
3029	3045	16	Fine gry.sd.w/oil stain(Q	ueen)			
3045	3050	5	Anhy.				
	1				·		
					-		
						1	