



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **New Mexico**
Lease No. **N. M. -03844**
Unit **Malco**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 26, 1955

Well No **3** **Federal Malco** is located **330** ft. from **N** line and **1650'** ft. from **E** line of sec. **27**
NW/NE of Sec 27 **13S** **31-E** **N.M.P.M.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Drickey **Chaves** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **4431** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Propose to drill 12 1/4 hole to 310', set 9" OD, AO #, at 310', circulate cement to surface. Drill 7 7/8" hole to approximately 3100', set 6", 18#, at 3100', cement with 150 sacks. Complete in Queen Sand through perforations of 6". Well to be drilled with rotary tools and to be known as Morris F. Antweil, Malco Federal No. 3.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **MORRIS F. ANTWEIL, OIL OPERATOR**
Address **P. O. BOX 1058**
HOBBS, NEW MEXICO
By **A. C. DAVIS, JR.**
Title **PROFESSIONAL GEOLOGIST**