


Form 9-331a
(Feb. 1951)

(SUBMIT IN TRIPLICATE)

Land Office New Mexico
Lease No. 03927
Unit Government "C"
Cities Service Oil Co.

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

57111 11:43



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	X
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<u>Subsequent Report of Spudding</u>	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 7, 19 55

Well No. 6 is located 1980 ft. from N line and 1980 ft. from E line of sec. 33
NW SE 33 (1/4 Sec. and Sec. No.) 13S (Twp.) 31E (Range) NMPH (Meridian)
Drickey-Queen (Field) Chaves (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 4280 ft. (Est.)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

This well was spudded at 2:00 P.M. March 5, 1955. Ran 175.77' of 8 5/8" OD 24# SS J-55 SS casing set at 187' and cemented with 125 sacks of neat cement. Cement circulated. Plug was down at 11:00 P.M. March 5, 1955. Cement was allowed to set 24 hours before testing for shut-off. Test was satisfactory. Drilling resumed.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Cities Service Oil Company
Address Box 97
Hobbs, New Mexico
By [Signature]
Title Dist. Supt.