


Form 9-331a
(Feb. 1951)



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office New Mexico

Lease No. 03927

Government Oil

Cities Service Oil Co.

1:27

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 2, 19 55

Well No. 2 is located 660 ft. from N line and 660 ft. from E line of sec. 34
34 (1/4 Sec. and Sec. No.) 13-0 (Twp.) 31-0 (Range) W (Meridian)
Brickey-Seen (Ext.) (Field) Chaves (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 4250 ft. (Est.)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

This well was drilled to 2924' in anhydrite. Ran 85.5 joints, 2908.22' of 5 1/2" ID 11.5 lb J-55 set at 2918' and cemented with 300 sacks of neat cement. Plug was down at 5:30 P.M. January 20, 1955. Cement was allowed to set 48 hours before testing for shut-off. Test was satisfactory and drilling was resumed.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Cities Service Oil Company

Address Box 77

Notas, New Mexico

By [Signature]

Title Asst. iv. Supt.