

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Hew	Hea	de)
Lease No	03%	27		
Unit GOV	e l'inin	ent	*C	i
Cities 3	arvi	ce (11	Co.

NOTICE OF INT	TENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT	-OFF
	TENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OF	
	TENTION TO TEST WATER SHUT-O		SUBSEQUENT REPORT OF ALTERING CA	
	TENTION TO RE-DRILL OR REPAIR		SUBSEQUENT REPORT OF RE-DRILLING	
	TENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONME	
	TENTION TO PULL OR ALTER CASI		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INT	TENTION TO ABANDON WELL			
*				
	(INDICATE ABOVE E	BY CHECK MARK NAT	JRE OF REPORT, NOTICE, OR OTHER DATA)
		v - -	February 7	, 19. 5
Vell No.	4 is located 18	60 ft. from (5	line and 2080 ft. from	w line of sec. 34
NIS SA	and Sec. No.) (T	3-5 31	ce) (Meridian)	
V-	neen (Ext.)	Chaves	io io	xico
	Field)	(County or Sub	division) (Stat	e or Territory)
	ing	sands; show sizes, we points, and all other	OF WORK eights, and lengths of proposed casings; important proposed work)	
This well OD 14% 8 cement. set 48 b	ings 1 was drilled to 30 10 J-55 SS casing so Flug was down at 1	sands; show sizes, woodness, and all other 037' in anhy et at 3034' 4:00 F.R. Fe	eights, and lengths of proposed casings;	s, 3025' of 5½" sacks of neat t was allowed to
This well OD 14% 8 cement. set 48 b	ings 1 was drilled to 30 1 J-55 SS casing so Flug was down at a ours before testing	sands; show sizes, woodness, and all other 037' in anhy et at 3034' 4:00 F.R. Fe	drite. San 91.6 joint and comented with 300 bruary 4, 1955.	s, 3025' of 5½" sacks of neat t was allowed to
This well OD 14% 8 cement. set 48 b	ings 1 was drilled to 30 1 J-55 SS casing so Flug was down at a ours before testing	sands; show sizes, woodness, and all other 037' in anhy et at 3034' 4:00 F.R. Fe	drite. San 91.6 joint and comented with 300 bruary 4, 1955.	s, 3025' of 5½" sacks of neat t was allowed to
This well OD 14% 8 cement. set 48 h	I was drilled to 30 J-55 SS casing so Flug was down at a curs before testing resused.	sands; show sizes, we points, and all other 037' in anhyet at 3034' 4:00 F.R. Fe	drite. San 91.6 joint and comented with 300 bruary 4, 1955.	s, 3025' of 52" sacks of neat t was allowed to satisfactory.
This well OD 14/8 cement. set 48 h Drilling	I was drilled to 30 J-55 SS casing so Flug was down at a curs before testing resused.	sands; show sizes, we points, and all other of the sand all other ot	drite. San 91.6 joint and comented with 300 bruary 4, 1955. Comented was shown aff. Shut-off test was	s, 3025' of 52" sacks of neat t was allowed to satisfactory.
This well OD 14% 8 cement. set 48 h Prilling	I was drilled to 30 J-55 SS casing so Flug was down at lours before testing resused.	sands; show sizes, we points, and all other of the sand all other ot	drite. San 91.6 joint and comented with 300 bruary 4, 1955. Comented was shown aff. Shut-off test was	s, 3025' of 5½" sacks of neat t was allowed to satisfactory.
This well OD 14/8 cement. set 48 h Drilling	1 was drilled to 30 J-55 SS casing so Flug was down at a curs before testing resused. that this plan of work must reconciled Service (sands; show sizes, we points, and all other of the sand all other other of the sand all other ot	drite. San 91.6 joint and comented with 300 bruary 4, 1955. Comented was shown aff. Shut-off test was	s, 3025' of 52" sacks of neat t was allowed to satisfactory.
This well OD 14% 8 cement. set 48 h Prilling	1 was drilled to 30 J-55 SS casing so Flug was down at a curs before testing resused. that this plan of work must reconstruct the Service (Box 97	sands; show sizes, we points, and all other of the sand all other other of the sand all other ot	eights, and lengths of proposed casings; important proposed work) drite. San 91.6 joint and comented with 300 bruary 4, 1955. Comented with 3	s, 3025' of 52" sacks of neat t was allowed to satisfactory.