



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office

Lease No. LC-062476

Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOWING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Conversion To Water Injection</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 12, 1961

Federal "V"
Well No. 3-34 is located 1980 ft. from N line and 1980 ft. from E line of sec. 34
SE/ of 34 13-S 81-E NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Caprock Queen Chaves New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 4428 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Rigged up pulling unit on September 12, 1961 and pulled sucker rods and tubing. Sand pumped well bore to total depth of 3061'. Ran 89 jts. 2-3/8" EUE 8rd. thd. J-55 Cement Lined tubing and one 5 1/2" 14# x 2" EUE 8rd. Haliburton R-3 packer. Landed packer @ 2626'. Tested packer for leaks, found none. Injection Began September 19, 1961. Have established an approximate rate of 400 barrels per day.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company John H. Trigg Company

Address Post Office Box 106

Maljamar, New Mexico

By K. E. Lester

Title Production Clerk