

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las Cruces  
Lease No. 062476  
Unit \_\_\_\_\_

# SUNDRY NOTICES AND REPORTS ON WELLS

|  |                                     |  |  |
|--|-------------------------------------|--|--|
| NOTICE OF INTENTION TO DRILL _____                   | <input checked="" type="checkbox"/> | SUBSEQUENT REPORT OF WATER SHUT-OFF _____        |  |
| NOTICE OF INTENTION TO CHANGE PLANS _____            |                                     | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING _____ |  |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF _____     |                                     | SUBSEQUENT REPORT OF ALTERING CASING _____       |  |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL _____ |                                     | SUBSEQUENT REPORT OF REDRILLING OR REPAIR _____  |  |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE _____        |                                     | SUBSEQUENT REPORT OF ABANDONMENT _____           |  |
| NOTICE OF INTENTION TO PULL OR ALTER CASING _____    |                                     | SUPPLEMENTARY WELL HISTORY _____                 |  |
| NOTICE OF INTENTION TO ABANDON WELL _____            |                                     |  |  |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 14, \_\_\_\_\_, 19 55

Federal "V" Lease  
Well No. 3-34 is located 1980 ft. from N line and 1980 ft. from E line of sec. 34

13-34 (4 Sec. and Sec. No.) 13 South (Twp.) 31 East (Range) N.M.P.M. (Meridian)

Dickey Queen (Field) Chaves (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 4424 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

I propose to drill this well to a depth of 3075 feet, with rotary to be used to a depth of 1420 feet, and cable tools from that point to total depth.

Surface casing, 13-3/8ths, will be run to a depth of 225 feet and sufficient cement used to circulate to the surface. This should require 225 sacks.

An intermediate string, 8-5/8ths, will be run to a depth of 1420 feet, mudded, and pulled after the oil string has been cemented.

Oil string, 5-1/2, will be run to a depth of 3044 feet, and cemented with 100 sacks.

All casing run and cemented will conform with the regulations set out by the Geological Survey.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company John H. Trigg

Address 705 Anherst Drive SE, Albuquerque, New Mexico

By John H. Trigg  
Title owner