

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
E-8333-1

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> GAS <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> P & A	7. Unit Agreement Name
2. Name of Operator Weldon S. Guest & I. J. Wolfson	8. Farm or Lease Name Drickey Queen Sand Unit Tr 42
3. Address of Operator c/o Oil Reports & Gas Services, Inc., Box 763, Hobbs, N.M.	9. Well No. 1
4. Location of Well UNIT LETTER C 330 FEET FROM THE North LINE AND 1650 FEET FROM THE West LINE, SECTION 2 TOWNSHIP 14 S RANGE 31 E NMPM.	10. Field and Pool, or Wildcat Caprock Queen
15. Elevation (Show whether DF, RT, GR, etc.) 4413 DF	12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Re-enter & salvage casing

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Subject well was plugged 11/70 by Cities Service Oil Company by setting cast iron bridge plug @ 3000 capped with 25 sacks cement and a 10 sack surface plug.

It is proposed to re-enter, shoot off 7" casing at 2000, spot 100' plug across casing stub, 100' plug across top of salt at 1500, 100' plug across 12 3/4" casing @ 290, 10 sack plug at surface. In this manner 2000' of 7" casing will be salvaged and the well more properly plugged to protect surface water.

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u><i>Wesley Hall</i></u>	TITLE <u>Agent</u>	DATE <u>10/18/73</u>
APPROVED BY <u>Joe D. Ramey</u>	TITLE <u>Dist. 2, Supv.</u>	DATE <u>10/18/73</u>
CONDITIONS OF APPROVAL, IF ANY:		