

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

1994 AUG 19 PM 2:10
WELL RECORD

N.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

Texas Pacific Coal and Oil Company (Company or Operator) N.M. State "H" A/c 1 (Lease)

Well No. 1-A, in SW 1/4 of SE 1/4, of Sec. 2, T. 18-S, R. 31-E, NMPM.
Drickey Queen Pool, Chaves County.

Well is 710 feet from South line and 1980 feet from East line of Section 2. If State Land the Oil and Gas Lease No. is

Drilling Commenced July 9, 1954 Drilling was Completed July 29, 1954

Name of Drilling Contractor Cactus Drilling Company

Address Hobbs, New Mexico

Elevation above sea level at Top of Tubing Head 4398' The information given is to be kept confidential until, 19

OIL SANDS OR ZONES

No. 1, from 3078' to 3092' No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
13 3/8"	34.5#	New	269'	Baker			
8 5/8"	28#	New	1436'	Baker	1436'		
5 1/2"	14#	New	3045'	Baker			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17 1/2"	13 3/8"	277'	275			
11"	8 5/8"	1443'	Mud			
7 7/8"	5 1/2"	3047'	100		Top Cement @ 2730'	

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

5 gals. per hour natural. Sandfrac treatment with 4000 gallons oil and 4000# of sand.

Result of Production Stimulation 18.48 BOPD

Depth Cleaned Out

I ORD OF DRILL-STEM AND SPECIAL TES

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 1443' feet, and from feet to feet.
Cable tools were used from 1443' feet to 3092' feet, and from feet to feet.

PRODUCTION

Put to Producing August 9, 1954

OIL WELL: The production during the first 24 hours was 72 barrels of liquid of which % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity 31.6

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	1430'	T. Devonian	T. Ojo Alamo
T. Salt	1490'	T. Silurian	T. Kirtland-Fruitland
B. Salt	2130'	T. Montoya	T. Farmington
T. Yates	2300'	T. Simpson	T. Pictured Cliffs
T. 7 Rivers		T. McKee	T. Menefee
T. Queen	3075'	T. Ellenburger	T. Point Lookout
T. Grayburg		T. Gr. Wash	T. Mancos
T. San Andres		T. Granite	T. Dakota
T. Glorieta		T.	T. Morrison
T. Drinkard		T.	T. Penn
T. Tubbs		T.	T.
T. Abo		T.	T.
T. Penn		T.	T.
T. Miss		T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1430	1430	Red Bed				
1430	1490	60	Anhydrite				
1490	2130	640	Salt				
2130	2300	170	Anhydrite & Salt				
2300	2550	250	Sand & Anhydrite				
2550	3075	525	Anhydrite, sand & salt				
3075	3092	17	Sand				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far
as can be determined from available records.

August 18, 1954 (Date)
Company or Operator Texas Pacific Coal & Oil Co. Address P.O. Box 1688 Hebbs, New Mexico
Name John Yuronda Position or Title District Engineer