


Form 9-381a
(Feb. 1951)



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. LC 068474
Unit Government "B"

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 23, 1954

Well No. 6 is located 660 ft. from S line and 660 ft. from E line of sec. 3
SE SE 3 14S 31E NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Drickey-Queen Chaves New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 44 19 ft. Estimated

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is proposed to drill this well to an approximate total depth of 3050' in the Queen Sand.

Size of Casing	Weight Per Foot	Depth	Cement
13 3/8" OD	36# and/or 48#	300'	Cemented-circulate
8 5/8" OD	24#	Est. 1375'*	Mudded
5 1/2" OD	14#	3000'	150 sacks **

* 8 5/8" OD casing will be reclaimed
 ** Mud ahead of cement

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Cities Service Oil Company

Address Box 97
Hobbs, New Mexico

By [Signature]
 Title Division Clerk

