



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office **Las Cruces**

Lease No. **LC 068474**

Unit **Government "B"**

**Cities Service Oil Co.**

1954 AUG 20 AM 9:49

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

**August 18**, 19**54**

Well No. **10** is located **1900** ft. from **NE** line and **1900** ft. from **E** line of sec. **1**

**NW SE 3** (1/4 Sec. and Sec. No.) **14S** (Twp.) **31E** (Range) **NM PM** (Meridian)  
**Brickey-Queen (Ext.)** (Field) **Chaves** (County or Subdivision) **New Mexico** (State or Territory)

The elevation of the derrick floor above sea level is **4425** ft. **DP**

### DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Total depth 3032' in Anhydrite. Ran 97.4 joints of 5 1/2" OD 14# SS J-35 SS Casing, 3022' set at 3029.5' and cemented with 300 sacks. Plug was down August 15, 1954. Cement was set 48 hours before testing for casing shut-off. Test was satisfactory. Drilling resumed.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Cities Service Oil Company**

Address **Box 97**

**Hobbs, New Mexico**

By 

Title **Asst. Division Supt.**