


Form 9-381a
(Feb. 1951)



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Las Cruces**
Lease No. **LC 060474**
Unit **Government "B"**
Cities Service Oil Co.

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 16, 19**54**

Well No. **24** is located **664.75** ft. from **N** line and **640** ft. from **W** line of sec. **3**

34 Sec. and Sec. No. **14-S** (Twp.) **31-E** (Range) **NMPN** (Meridian)
Drikey-Queen (Field) **Chaves** (County or Subdivision) **New Mexico** (State or Territory)

The elevation of the derrick floor above sea level is **4277** ft. (Nat.)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

This well was drilled to 171' in red bed. Ran 4 joints, 160.55', of 8 5/8" OD 22.7# 54 SJ casing set at 171' and cemented with 100 sacks of neat cement. Cement circulated. Plug was down at 3:00 A.M. December 14, 1954. Cement was allowed to set 30 hours before testing for shut-off. Test was satisfactory. Drilling resumed.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Cities Service Oil Co.**

Address **Box 97**

Hobbs, New Mexico

By

Title **Asst. Div. Supt.**