

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOCATE WELL CORRECTLY

Signed John W. Kuehn

The summary on this page is for the condition of the well at above date

Commenced drilling June 19, 1958 Finished drilling June 26, 1958

(Denote gas by G)

No. 1, from 2806 to 2816 No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

No. 1, from _____ to _____ No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

[illegible]

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
5-8"	102'	50	Pump		
5-1/2"	2825'	100	Pump		

Heaving plug—Material _____ Length _____ Depth set _____
Adapters—Material _____ Size _____

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out

Rotary tools were used from 0 feet to 2825 feet, and from _____ feet to _____ feet
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

----- July 28 -----, 1958 ----- Put to producing ----- July 11 -----, 1958 -----

The production for the first 24 hours was * 35 barrels of fluid of which 100 % was oil; _____ % emulsion; _____ % water; and _____ % sediment. Gravity, °Bé. _____

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in. _____

Jack Henderson, Driller G. F. Shynes, Driller
J. E. Massingill, Driller _____, Driller

FROM—	TO—	TOTAL FEET	FORMATION
0	1110	1110	Red Beds
1110	1170	60	Anhydrite
1170	1230	60	Anhydrite and Shale
1230	1880	650	Salt, potash, anhydrite shells
1880	2800	920	Anhydrite and Shale
2800	2825	25	Sand and Shale
T. D. 2825'			
Gamma Ray Log Tops:			
Anhydrite	1125	+ 3073	
Salt	1243	+ 2955	
Base Salt	1881	+ 2317	
Yates	2033	+ 2165	
Queen P.	2796	+ 1402	

