


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **062486**
Lease No. _____
Unit _____



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 15, 1955

Federal-trigg
Well No. **16-4** is located **660** ft. from **N** line and **1980** ft. from **E** line of sec. **4**
SE/4 Sec. 4 **14-3** **31-E** **N.W.P.M.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
(Driskay) Caprock **Chaves** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **4198** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

I propose to drill a well to a depth of 2850', using combination tools.

8-5/8" casing will be set into the red beds to a depth of 100 feet and cemented with 50 sacks.

Rotary tools will be used until the Anhydrite cap above the pay sand is reached at approximately 2796 feet.

5 1/2" casing will be cemented in this cap with 100 sacks.

I will drill into the pay sand with cable tools.

All casing will be set and cemented in accordance with the regulations set out by the U. S. Geological Survey.

Company **John H. Trigg Co.**

Address **P. O. Box 5629**
Boswell, New Mexico

By **John H. Trigg**
Title **Owner**