

APPROVED
JUL 11 1962RONNIE E. SHOOK
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office **Las Cruces**
Lease No. **LC-962486**
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	
Notice of intention to drill deeper & repair cement job	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 14, 1962

Well No. **23** is located **1989.5** ft. from **[N]** line and **2310** ft. from **[W]** line of sec. **4**

4 **14-S** **31-E** **NMPM**

(¼ Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Caprock Queen **Chaves** **New Mexico**

(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **4177** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Ran Wright Survey's Flow Meter. Determined that 80% of injected water was escaping around the casing shoe. We propose to drill to an approximate total depth of 2815' in order to set a 3" liner and cement off thief zone. Present total depth is now 2799'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **JOHN H. TRIGG COMPANY**Address **Box 106****Maljamar, New Mexico**By *[Signature]*Title **FIELD Production Clerk**