



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las Vegas

Lease No. 668400

Unit                     

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF ALTERING CASING.....	<input type="checkbox"/>
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF ABANDONMENT.....	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	<input type="checkbox"/>	SUPPLEMENTARY WELL HISTORY.....	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL.....	<input type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 18, 19 55

Trigg Federal

Well No. 2-9 is located 800 ft. from [N] line and 1000 ft. from [E] line of sec. 9

SW 1/4 Sec. 9 14 South 31 East 1-10-55  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Brikey Queen Leaves New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is              ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

I propose to drill this well to a depth of 2815 feet, with rotary to be used to a depth of 1160 feet, and cable tools from that point to total depth.

Surface casing, 13-3/8", will be run to 120 feet, set in the red beds, and cemented with 50 sacks.

The intermediate string, 8-5/8", will be run to a depth of 1160 feet in to anhydrite, and mudded.

The oil string, 5-1/2", will be run to a depth of 2765 feet, set in the anhydrite cap overlying the Queen sand, and cemented with 100 sacks.

All casing run and set will be under methods approved by the Geological Survey.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company John H. Trigg

Address 725 Ashurst Drive N.E., Albuquerque, New Mexico

By John H. Trigg  
Title Owner