Form	9-331 a
(Feb	. 1951)

	 0	

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	IA8	Cruces
Lease No	062	¥8 <b>6</b>
Unit		

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		
	-	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	X	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.		SUBSEQUENT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING.		SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL		
(INDICATE ABOVE BY CHECK M	ARK NAT	URE OF REPORT, NOTICE, OR OTHER DATA)
		10
		Jaunary 7, 19 56
		line and $1280$ ft. from $\begin{bmatrix} E \\ W \end{bmatrix}$ line of sec.
3 14 South	(R)	(e) Meridian o ito
Cap <b>roak</b> , ween (Ci	PY BI	division) (S. T.
The elevation of the derrick floor above sea	level	is the ft.
DET	AILS	OF WORK
(State names of and expected depths to objective sands; shov ing points, and	sizes, w all other	eights,'and lengths of proposed casings; indicate mudding jobs, cement- important proposed work)
I propose to drill this w	:11 1	to a total depth of 2810 feet, with
that point to total depth, urface easing will be run cemented with 50 sacks, where oil string will be run	to ito iich iich ito ihis	a depth of 100 feet, 8-5/8", and will circulate to the surface. a depth of 2770 feet, 5-1/2", and pipe will be set in the anhydrite and.
that point to total depth, urface easing will be rus cemented with 50 sacks, whe oil string will be rus cemented with 100 sacks. This well will be drilled All easing run and cemented Geological Survey Office.	to t	of 2700 feet, and cable tools from a depth of 100 feet, 8-5/8°, and will circulate to the surface. a depth of 2770 feet, 5-1/2°, and pipe will be set in the anhydrite and. With cable tools.
that point to total depth, urface easing will be run cemented with 50 sacks, whe oil string will be run cemented with 100 sacks. The caprock overlying the Queen This well will be drilled.  All easing run and cemente Geological Survey Office.  I understand that this plan of work must receive approve	to t	a depth of 100 feet, 8-5/8°, and will circulate to the surface. a depth of 2770 feet, 5-1/2°, and pipe will be set in the anhydrite and.
that point to total depth, urface easing will be run cemented with 50 sacks, whe cil string will be run cemented with 100 sacks. The caprock overlying the Queet This well will be drilled.  All easing run and cemented Geological Survey Office.  I understand that this plan of work must receive approve Company. John H. Trigg.	oth (  i to ii oh i to ihis in si in i	a depth of 100 feet, 8-5/8°, and will circulate to the surface. a depth of 2770 feet, 5-1/2°, and pipe will be set in the anhydrite and. With cable tools.  It be under methods approved by the ing by the Geological Survey before operations may be commenced.
that point to total depth, urface easing will be run cemented with 50 sacks, whe cil string will be run cemented with 100 sacks. The caprock overlying the Queet This well will be drilled.  All easing run and cemented Geological Survey Office.  I understand that this plan of work must receive approve Company. John H. Trigg.	oth (  i to ii oh i to ihis in si in i	a depth of 100 feet, 8-5/8", and will circulate to the surface. a depth of 2770 feet, 5-1/2", and pipe will be set in the anhydrite and. With cable tools.  It be under methods approved by the ing by the Geological Survey before operations may be commenced.
that point to total depth, urface easing will be run cemented with 50 sacks, whe oil string will be run cemented with 100 sacks. The oil string will be run cemented with 100 sacks. This well will be drilled All easing run and cemented Geological Survey Office.  I understand that this plan of work must receive approve Company	oth (  i to ii oh i to ihis in si in i	a depth of 100 feet, 8-5/8", and will circulate to the surface. a depth of 2770 feet, 5-1/2", and pipe will be set in the anhydrite and. With cable tools.  It be under methods approved by the ing by the Geological Survey before operations may be commenced.
that point to total depth, urface easing will be run cemented with 50 sacks, whe oil string will be run cemented with 100 sacks. The oil string will be run cemented with 100 sacks. This well will be drilled All easing run and cemented Geological Survey Office.  I understand that this plan of work must receive approve	oth (  i to ii oh i to ihis in si in i	a depth of 100 feet, 8-5/8°, and will circulate to the surface. a depth of 2770 feet, 5-1/2°, and pipe will be set in the anhydrite and. With cable tools.  It be under methods approved by the ing by the Geological Survey before operations may be commenced.