



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. LC 068474
Unit Government "A"
Cities Service Oil Co.

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 16, 1954

Well No. 7 is located 1980 ft. from (N) line and 4620 ft. from (E) line of sec. 10
SW 1/4 10 14S 31E RMPM
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Brickley-Usen Chaves New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 4272 ft. (1st.)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is proposed to drill this well to an approximate total depth of 3000' in the Queen Sand.

Size of Casing	Weight Per Foot	Depth	Cement
13 3/8" CD	30 and/or 48	300'	Cemented-circulate
8 5/8" CD	24	1st. 1290'	Mudded
5 1/2" CD	14	2950'	150 sacks

* 8 5/8" CD casing will be reclaimed.

** Mud ahead of cement.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Cities Service Oil Company

Address Box 97

Hobbs, New Mexico

By [Signature]

Title Asst. Div. Mgt.