NEW MEXICO DIL CONSERVATION COMMISSION Sazta Fe, New Mexico

	tions in the		s approved should be follo tions of the Commission.	owed, and work	k should	not begin until approval is ol	btained. See addi-
			Indicate Nature of N	otice by Check	ing Bel) w	
Notice of In TO Change P			NOTICE OF INTENTION TEMPORABILY ABANDO			Notice of Intention to Drill Deeper	
NOTICE OF INTO PLUG WEL			Notice of Intention to Plug Fack			Notice of Intention to Set Liner	
Notice of In To Squeeze	TENTION		Notice o Intention to Acidiz i			Notice of Intention to Shoot (Nitro)	
Notice of In to Gun Perf			Notice of Intention (Other) Fractur		x	Notice of Intention (Other)	
		COMMISSION	Unhha Ma	bardaa		Samuel /	nord
SANTA FE,	NEW MEX	ICO	Hobbs, Ne	W MEXICO Place)		Parch 6,	***TA20******
Gentlemen:							
Following	g is a Notic	e of Intention to d	lo certain work as describ	ed below at the	·		
	all and the	(Company or Operato	F)	Lease	LII A.II	.Well No3in.	(Unit)
(40-acre	Subdivision)	¼ of Sec	11, T14=S,	R. 31-6	MPM.,	Caprock Queen	Poo
	Che	¥8\$ Cd	ounty.				
		FU)	LL DETAILS OF PR	OPOSED PL	AN OI	WORK	
			LL DETAILS OF PROVINSTRUCTIONS IN				
	in or	(FOLLOV	V INSTRUCTIONS IN	THE RULES	AND R		follows:
	_	(FOLLOW) der to incre	v INSTRUCTIONS IN	THE RULES	AND R	EGULATIONS)	follows:
	1 _{n or}	(FOLLOW) der to incre Full rods,	v instructions in ease production in pump and 2-3/8"	THE RULES s is proportubing.	AND R	egulations) co fracture treat as	
	1.	der to incre Full rods, Run steel l Treat open	v instructions in case production in pump and 2-3/8" ine measurement. hole from 3067-3	THE RULES s is proportubing. Clean or US2! with	AND Rosed t	EGULATIONS)	ssary.
	1. 2. 3.	der to incre Full rods, Run steel l Treat open Adomite wit	v instructions in ease production i pump and 2-3/8" ine measurement. hole from 3067-3. h l# sand per ga	tubing. Clean or US2! with	AND Rosed t	egulations) to fracture treat as the sand pump if neces	ss ar y.
	1. 2.	der to incre Full rods, Run steel l Treat open Adomite wit	v instructions in case production in pump and 2-3/8" ine measurement. hole from 3067-3	tubing. Clean or US2! with	AND Rosed t	egulations) to fracture treat as the sand pump if neces	ss ar y.
	1. 2. 3.	der to incre Full rods, Run steel l Treat open Adomite wit	v instructions in ease production i pump and 2-3/8" ine measurement. hole from 3067-3. h l# sand per ga	tubing. Clean or US2! with	AND Rosed t	egulations) to fracture treat as the sand pump if neces	ss ar y.
	1. 2. 3.	der to incre Full rods, Run steel l Treat open Adomite wit	v instructions in ease production i pump and 2-3/8" ine measurement. hole from 3067-3. h l# sand per ga	tubing. Clean or US2! with	AND Rosed t	egulations) to fracture treat as the sand pump if neces	ssary.
	1. 2. 3.	der to incre Full rods, Run steel l Treat open Adomite wit	v instructions in ease production i pump and 2-3/8" ine measurement. hole from 3067-3. h l# sand per ga	tubing. Clean or US2! with	AND Rosed t	egulations) to fracture treat as the sand pump if neces	ss ar y.
	1. 2. 3.	der to incre Full rods, Run steel l Treat open Adomite wit Rerun rods,	v instructions in ease production i pump and 2-3/8" ine measurement. hole from 3067-3. h l# sand per ga	tubing. Clean or US2! with	AND Rosed t	egulations) to fracture treat as the sand pump if neces	ss ar y.
	1. 2. 3.	der to incre Full rods, Run steel l Treat open Adomite wit Rerun rods,	v instructions in ease production i pump and 2-3/8" ine measurement. hole from 3067-3. h l# sand per ga	tubing. Clean or US2! with	AND Rosed t	egulations) to fracture treat as the sand pump if neces	ss ar y.
	1. 2. 3. 4.	der to incre Full rods, Run steel l Treat open Adomite wit Rerun rods,	vinstructions in ease production in pump and 2-3/8" ine measurement. hole from 3067-3 in 1# sand per gamp and 2-3/8"	tubing. Ulean or US2! with tubing. Ulean or US2! with tubing.	and Rosed 1 ut wit	egulations) to fracture treat as the sand pump if neces	ss ar y.
	1. 2. 3. 4.	der to incre Full rods, Run steel l Treat open Adomite wit Rerun rods,	vinstructions in ease production in pump and 2-3/8" ine measurement. hole from 3067-3 in 1# sand per gamp and 2-3/8"	tubing. Ulean or US2! with tubing. Ulean or US2! with tubing.	and Rosed 1 ut wit	egulations) o fracture treat as in sand pump if neces o gallons lease oil	ss ar y.
	1. 2. 3. 4.	der to incre Full rods, Run steel l Treat open Adomite wit Rerun rods,	vinstructions in ease production in pump and 2-3/8" ine measurement. hole from 3067-3 in 1# sand per gamp and 2-3/8"	tubing. Ulean on US2' with tubing. Ulon. Guli	AND Rosed to	corporation Company or Operator	ss ar y.
Except as foll Approved	1. 2. 3. 4.	der to incre Full rods, Run steel l Treat open Adomite wit Rerun rods,	vinstructions in ease production in pump and 2-3/8" ine measurement. hole from 3067-3 in 1# sand per gamp and 2-3/8"	tubing. Ulean on US2' with tubing. Ulon. Guli	AND Rosed to	egulations) o fracture treat as in sand pump if neces o gallons lease oil	seary.
Approved Except as foll Approved OIL CONSE	1. 2. 3. 4.	der to incre Full rods, Run steel l Treat open Adomite wit Rerun rods,	vinstructions in ease production in pump and 2-3/8" ine measurement. hole from 3067-3 in 1# sand per gamp and 2-3/8"	tubing. Ulean on US2' with allon. Tubing. Guli	AND Rosed to the with a control of the control of t	corporation Company of Prod.	seary. containing

Address Box 2167, Hobbs, New Mexico