



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____

Lease No. **18-068361**

Unit **068 264**

SUNDRY NOTICES AND REPORTS ON WELLS

| | | |
|--|--|-------------------------------------|
| NOTICE OF INTENTION TO DRILL | SUBSEQUENT REPORT OF WATER SHUT-OFF | |
| NOTICE OF INTENTION TO CHANGE PLANS | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | SUBSEQUENT REPORT OF ALTERING CASING | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | SUBSEQUENT REPORT OF ABANDONMENT | <input checked="" type="checkbox"/> |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | SUPPLEMENTARY WELL HISTORY | |
| NOTICE OF INTENTION TO ABANDON WELL | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 18, 19**57**

Well No. **1** is located **660** ft. from **N** line and **2310** ft. from **E** line of sec. **20**

W/4 (1/4 Sec. and Sec. No.) **11S** (Twp.) **31E** (Range) **N.M.P.M.** (Meridian)
Caprock (Field) **Chavez** (County or Subdivision) **New Mexico** (State or Territory)

The elevation of the derrick floor above sea level is **4115** ft. **G.L.**

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Surface casing - 805/8 set 220' and cemented w/150 sacks by Halliburton.
Queen sand dry and following abandonment plugs of cement set as follows:

T.D. 2769 - 2720 with 15 sacks (Queen sand 2734-41)
2720 - 240 Mud
240 - 200 with 15 sacks
200 - 20 Mud
30 - Surface with 10 sacks

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **T.F. Hodge**

Address **1113 Continental Bank Building**

Fort Worth 2, Texas

By **K. K. Amis**

Title **Petroleum Engineer**