



AREA 640 ACRES  
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD 59

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

Byard Bennett

(Company or Operator)

Zimmerman

(Lease)

Well No. 2-A, in NE 1/4 of SW 1/4, of Sec. 21, T. 14 S, R. 31 E, NMPM.

Caprock-Queen

Pool,

Chaves

County.

Well is 1650 feet from South line and 2310 feet from West line

of Section 21. If State Land the Oil and Gas Lease No. is

Drilling Commenced Sept. 30, 1958 Drilling was Completed Oct. 8, 1958

Name of Drilling Contractor Donnelly Drilling Co., Inc.

Address Artesia, New Mexico

Elevation above sea level at Top of Tubing Head 4,220 The information given is to be kept confidential until

, 19

OIL SANDS OR ZONES

No. 1, from 2,894 to 2,904 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8	24	Used	176	Reg.			Surface
5-1/2	14	New	2906	HOWCO		2894-2899	Production

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12-1/4	8-5/8	176	100	Halliburton		
7-7/8	5-1/2	2906	125	Halliburton		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Sand-frac thru perforations from 2894-2899 w/4000 gal. oil

and 4,000# sand.

Result of Production Stimulation Swabbed 65 Bbl. of new oil after recovering load oil.

Depth Cleaned Out 2906

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

Rotary tools were used from 0 feet to 2906 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.  
Cable tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.

Put to Producing Oct. 18, 19 58

OIL WELL: The production during the first 24 hours was 65 barrels of liquid of which 100 % was oil; 0 % was emulsion; 0 % water; and 0 % was sediment. A.P.I. Gravity 34

GAS WELL: The production during the first 24 hours was.....M.C.F. plus.....barrels of liquid Hydrocarbon. Shut in Pressure.....lbs.

Length of Time Shut in.....

## Northwestern New Mexico

T. Anhy.....	T. Devonian.....	T. Ojo Alamo.....
T. Salt.....	T. Silurian.....	T. Kirtland-Fruitland.....
B. Salt..... <b>1,934</b>	T. Montoya.....	T. Farmington.....
T. Yates..... <b>2,113</b>	T. Simpson.....	T. Pictured Cliffs.....
T. 7 Rivers..... <b>2,334</b>	T. McKee.....	T. Menefee.....
T. Queen..... <b>2,894</b>	T. Ellenburger.....	T. Point Lookout.....
T. Grayburg.....	T. Gr. Wash.....	T. Mancos.....
T. San Andres.....	T. Granite.....	T. Dakota.....
T. Glorieta.....	T. ....	T. Morrison.....
T. Drinkard.....	T. ....	T. Penn.....
T. Tubbs.....	T. ....	T. ....
T. Abo.....	T. ....	T. ....
T. Penn.....	T. ....	T. ....
T. Miss.....	T. ....	T. ....

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

11/3/58  
(Date)

Company or Operator..... **Byard Bennett**

Name..... *Byard Bennett*

(Date) \_\_\_\_\_  
Address..... **Box 48 Roswell, N.M.**  
Position or Title..... **Operator**