

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOCATE WELL CORRECTLY

The summary on this page is for the condition of the well at above date,
 Commenced drilling April 28, 1955 Finished drilling May 6, 1955

(Denote gas by G)

(Denote gas by G)

3076	3124		
No. 1, from _____	to _____	No. 4, from _____	to _____
No. 2, from _____	to _____	No. 5, from _____	to _____
No. 3, from _____	to _____	No. 6, from _____	to _____

No. 1, from _____ to _____

No. 2, from _____ to _____

No. 3, from _____ to _____

No. 4, from _____ to _____

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
5/8"	24#	8rd.	E. W.	270	Larkin	--	--	--	
5/8"	1 1/4"	8rd.	E. W.	3077	HISTORY OF OIL OR GAS WELL				

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
5/8"	240'	200	pump of plug	---	Cement Circ.
1 1/2"	3077	150	" "	---	---

Heaving plug—Material Length Depth set

Adapters—Material Size

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out
Not Shot						

Rotary tools were used from 0 feet to 3124 feet, and from -- feet to -- feet.

Cable tools were used from -- feet to -- feet, and from -- feet to -- feet.

June 2, 1955 Put to producing June 1, 1955

The production for the first 24 hours was 80 barrels of fluid of which 100% was oil; 0% emulsion, 0% water; and 0% sediment. Gravity, °Bé. 35

If gas well, cu. ft. per 24 hours ----- Gallons gasoline per 1,000 cu. ft. of gas -----

Rock pressure, lbs. per sq. in. _____

Kerr-McGee Oil Ind.	Driller	Driller
	Driller	Driller

FROM—	TO—	TOTAL FEET	FORMATION
1376 2306 3076 Log Attached	3124		Rustler Yates Queen

