

(SUBMIT IN TRIPLICATE)

Land Office ArtesiaLease No. LC-070336AUnit Federal-MedlinUNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

|   |   |          |
|---|---|----------|
| NOTICE OF INTENTION TO DRILL.....                   | SUBSEQUENT REPORT OF WATER SHUT-OFF.....        |          |
| NOTICE OF INTENTION TO CHANGE PLANS.....            | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... |          |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....     | SUBSEQUENT REPORT OF ALTERING CASING.....       |          |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR..... |          |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....        | SUBSEQUENT REPORT OF ABANDONMENT.....           |          |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.....    | SUPPLEMENTARY WELL HISTORY.....                 |          |
| NOTICE OF INTENTION TO ABANDON WELL.....            | <u>Set liner to shut off water</u>              | <u>X</u> |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 6, 1955

Well No. 3 is located 2310 ft. from N line and 990 ft. from W line of sec. 22

W/4 22 11S 31E 11P  
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Caprock-Guerra Chaves New Mexico  
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 4426 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Verbal Permission to do the following obtained from John Frost on 9-2-55 per telephone conversation fly to Frost:

Pull tubing & rods. If necessary clean out to 3130'. Run 4" Hydril liner from 3050' to 3130' w/4" x 5 1/2" Brown type "C" liner hanger, 4" x 5 1/2" Brown type "P" packer and 4" type "V" set shoe. Cement liner 3130 to 3050 w/approx. 50 sacks cement. Drill out cement to 3120'. Jet perforate 4 holes per foot, 3140-3110'. If well does not produce naturally acidize or sand frac thru liner perforations.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Ada Oil Co. Inc.Address Box 126, Midland, TexasBy C. L. Fly Jr. (C. L. Fly Jr.)Title Chief Clerk