

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Morris H. Antweil

Medlin

(Company or Operator)

(Lease)

Well No. 1, in NE NE 22 14S 31E, T. Chaves, R. Chaves, NMPM.

Well is 330 feet from north line and 990 feet from east line of Section 22.

Drilling Commenced October 19, 1954. Drilling was Completed October 25, 1954.

Name of Drilling Contractor Jennings Drilling Company
Address Box 877, Hobbs, New Mexico

Elevation above sea level at Top of Tubing Head 4427 L.F.. The information given is to be kept confidential until , 19 .

OIL SANDS OR ZONES

No. 1, from 3092 to 3099. No. 4, from to .
No. 2, from to . No. 5, from to .
No. 3, from to . No. 6, from to .

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

None
No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
<u>5-5/8</u>	<u>24</u>	<u>Used</u>	<u>251.3</u>	<u>TP Guide</u>			
<u>3-1/2</u>	<u>15.5 & 14</u>	<u>Used</u>	<u>3086</u>	<u>Halco float</u>			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
<u>11</u>	<u>8-5/8</u>	<u>259.8</u>	<u>170</u>	<u>Pump & plug</u>	<u>9#/gal</u>	<u>75 ex.</u>
<u>7-7/8</u>	<u>5-1/2</u>	<u>3088</u>	<u>100</u>	<u>" "</u>	<u>10.2</u>	<u>Native</u>

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

No treatmentResult of Production Stimulation Depth Cleaned Out

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 3038 feet, and from feet to feet
 Cable tools were used from 3038 feet to 3099 feet, and from feet to feet

PRODUCTION

Put to Producing November 1, 1954

OIL WELL: The production during the first 24 hours was 49 barrels of liquid of which 100 was oil; % was emulsion; % water; and % was sediment. API Gravity

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy. 1420	T. Devonian	T. Ojo Alamo
T. Salt. 1575	T. Silurian	T. Kirtland-Fruitland
B. Salt. 2140	T. Montoya	T. Farmington
T. Yates	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	T. McKee	T. Menefee
T. Queen 3092	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres	T. Granite	T. Dakota
T. Glorieta	T.	T. Morrison
T. Drinkard	T.	T. Penn
T. Tubbs	T.	T.
T. Abo	T.	T.
T. Penn	T.	T.
T. Miss	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1420	1420	Red Bed				
1420	1575	155	Anhydrite				
1575	2140	565	Salt				
2140	2340	200	Anhydrite and Salt				
2340	2465	125	Sand and Anhydrite				
2465	3092	627	Salt, Sand & Shale				
3092	3099	7	Sand				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

November 1, 1954 (Date)

Company or Operator: FORTIS T. ANTELL
 Name: Ken Jennings

Address: Box 1055, Hobbs, New Mexico
 Position or Title: Agent