NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of easing shut-off, result of plugging of well

result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.			
	Indicate Nature of Report by Checking E	elow	
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON (Other)	Х
	12/3/54	Hobbs, New Mexi	CO (Place)
Following is a report on the work done	and the results obtained under the heading		(Flace)
Morris R. Antweil	Medlin (Lease)		
Jennings Drilling Co. (Contractor)	, Well No2	in the SE 1/4 NE 1/4	4 of Sec22
14S , R 31E , NMPM, Dric	ckey-Queen Pool, Pool,	Chaves	County.
'he Dates of this work were as folows			

otice of intention to do the work (was) (wa	s not) submitted on Form C-102 on		19
		(Cross out incorrect words)	, ,
nd approval of the proposed plan (was) (wa	s not) obtained.		
	s not) obtained. ACCOUNT OF WORK DONE AND RESI	ULTS OBTAINED	
DETAILED	ACCOUNT OF WORK DONE AND RES		
Surface casing tested i water shut off. Drille with 100 sx. We intend		and regulations. 26 lbs. used. S casing. if satis	et at 3088 factory.
Surface casing tested i water shut off. Drille with 100 sx. We intend	ACCOUNT OF WORK DONE AND REST in accordance with rules ed to depth of 3091', 7", i to wait on cement, test	and regulations. 26 lbs. used. S casing. if satis	et at 3088 factory.
Surface casing tested i water shut off. Drille with 100 sx. We intend	ACCOUNT OF WORK DONE AND REST in accordance with rules ed to depth of 3091', 7", i to wait on cement, test	and regulations. 26 lbs. used. S casing. if satis	et at 3088 factory.
Surface casing tested i water shut off. Drille with 100 sx. We intend	ACCOUNT OF WORK DONE AND REST in accordance with rules ed to depth of 3091', 7", i to wait on cement, test	and regulations. 26 lbs. used. S casing. if satis	et at 3088 factory.
Surface casing tested i water shut off. Drille with 100 sx. We intend	ACCOUNT OF WORK DONE AND REST in accordance with rules ed to depth of 3091', 7", i to wait on cement, test	and regulations. 26 lbs. used. S casing. if satis	et at 3088 factory.
Surface casing tested i water shut off. Drille with 100 sx. We intend	ACCOUNT OF WORK DONE AND REST in accordance with rules ed to depth of 3091', 7", i to wait on cement, test	and regulations. 26 lbs. used. S casing. if satis	et at 3088 factory.
Surface casing tested i water shut off. Drille with 100 sx. We intend	ACCOUNT OF WORK DONE AND REST in accordance with rules ed to depth of 3091', 7", i to wait on cement, test	and regulations. 26 lbs. used. S casing. if satis	et at 3088 factory.
Surface casing tested i water shut off. Drille with 100 sx. We intend drill out with cable to	in accordance with rules ed to depth of 3091', 7" is to wait on cement, testools to TD, approximately	and regulations. 26 lbs. used. S casing, if satis 3101 to test Que	et at 3088 factory, en Sand.
Surface casing tested i water shut off. Drille with 100 sx. We intend drill out with cable to	ACCOUNT OF WORK DONE AND REST in accordance with rules ed to depth of 3091', 7", i to wait on cement, test	and regulations. 26 lbs. used. S casing, if satis 3101 to test Que	et at 3088 factory, en Sand.
Surface casing tested in water shut off. Drille with 100 sx. We intend drill out with cable to with	Jennings Drilling (Company) In accordance with rules and to depth of 3091', 7" and to wait on cement, test to wait on cement, test to lead to TD, approximately the content of the conten	and regulations. 26 lbs. used. Straing, if satistrains and second secon	et at 3088 factory, en Sand.
Surface casing tested in water shut off. Drille with 100 sx. We intend drill out with cable to	Jennings Drilling (Company) In accordance with rules and to depth of 3091', 7" and to wait on cement, test to wait on cement, test to lead to TD, approximately the content of the conten	and regulations. 26 lbs. used. Straing, if satistically 3101 to test Que Co. Drilling Straing Strain	et at 3088 factory, en Sand.
Surface casing tested in water shut off. Drille with 100 sx. We intend drill out with cable to vitnessed by B. J. Tabor (Name)	Jennings Drilling (Company) I hereby certify the total content of the content of	and regulations. 26 lbs. used. Straing, if satistically 3101 to test Que One of Drilling Straing Str	et at 3088 factory, en Sand.
Surface casing tested in water shut off. Drille with 100 sx. We intend drill out with cable to vitnessed by B. J. Tabor (Name)	Jennings Drilling Company) I hereby certify the total control of the best of my Name	and regulations. 26 lbs. used. S casing, if satis 3101 to test Que Title at the information given above is knowledge.	et at 3088 factory, en Sand.
Surface casing tested in water shut off. Drille with 100 sx. We intend drill out with cable to with	Jennings Drilling Company) I hereby certify the to the best of my Name	and regulations. 26 lbs. used. Straing, if satistically 3101 to test Que One of Drilling Straing Str	et at 3088 factory, en Sand.