





Job separation sheet



UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY OBES OFFICE OCC

P. O. Box 187 1955 FEB 7 AM 8:00 Artesia, New Mexico

February 3, 1955

Mr. Morris R. Antweil Box 1058 Hobbs, New Mexico

Re: Oil and Gas Lease New Mexico O6173

Dear Sir:

Your "Subsequent Report of Abandonment" dated October 22, 1954, covering your well No. 1 Todhunter located in the NW1 NW1, section 23, T. 14 S., R. 31 E., Wildoxt Area, Chaves County, New Mexico, is hereby approved.

Very truly yours,

John A. Frost District Engineer

JAF:mm Inspected bby John A. Frost February 3, 1955



UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY 1 FOR

対抗な異性的では、CLATE AND VOICE AND LOCAL COLORS (A COLORS)

The Atlanta

Tankin in diponing of

o difitation di con**se**t Militario di serie

でから新しまし**な性性な** ということで、一つから音な**は**続い

> . १८ १८ १ क्षेत्र १४ - १८ १८ १८ १८ १८ १८ १८ १८ १८ १८ १८ १ क्षेत्र १४ १८ १८ १८ १८ १८ १८ १८ १८ १८ १८

Form 9-331a (Feb. 1951)

(SUBMIT IN TRIPLICATE)

UNITED STATES

and Office

N.M. 06173

Unit 000

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO CHANGE PLANS	 SUBSEQUENT REPORT OF WATER SHUT-OFF SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING SUBSEQUENT REPORT OF ALTERING CASING SUBSEQUENT REPORT OF REDRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

111 +		*************	September	20,	, 19 54	
Well No. is located	ted	$\operatorname{\mathbf{com}}\left\{egin{array}{c} \mathbf{N} \\ egin{array}{c} \mathbf{N} \end{array}\right\}$ line :	and 330 ft. fre	om $\left\{\begin{array}{c} \mathbf{W} \\ \mathbf{W} \end{array}\right\}$ line	of sec. 23	
(% Sec. and Sec. No.) Dricker Meen (EVV.)	14~S	11-2	H.Z.	, ,		
(1/4 Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)			
	Chaves			N.M.		
(Field)	(Count	y or Subdivision)		(State or Territory)		

The elevation of the derrick floor above sea level is 4400 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drill 11" hole to approximately 275°; set end coment to surface 275° of 8 5/8"-26%; drill 7 7/8" hole to approximately 3000° or depth sufficient to test the queen sand after setting and comenting with 150 sacks 52"-16% casing set at approximately 3000°.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.						
	terris a.					
Address	F. C. Box	1058				
	Hobbs, N.	**************************************	Byle. L. Chace			
			TitleAgent			