

COPIES RECEIVED	
TRIBUTION	
FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- <b>Water Injection</b>		7. Unit Agreement Name <b>Eastcap Queen</b>
2. Name of Operator <b>AGUA, INC.</b>		8. Farm or Lease Name
3. Address of Operator <b>Box #198, Artesia, New Mexico 88210</b>		9. Well No. <b>8</b>
4. Location of Well UNIT LETTER <b>G</b> , <b>1980</b> FEET FROM THE <b>North</b> LINE AND <b>1980</b> FEET FROM THE <b>East</b> LINE, SECTION <b>27</b> TOWNSHIP <b>14 South</b> RANGE <b>31 East</b> NMPM.		10. Field and Pool, or Wildcat <b>Caprock Queen</b>
15. Elevation (Show whether DF, RT, GR, etc.)		12. County <b>Chaves</b>

16.

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☒  
CHANGE PLANS ☐

### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This is a shut-in well. It is proposed to plug and abandon as follows:

Total Depth: 3122'.  
Surface Casing: 8-5/8" 24# at 328' w/175 sx.  
Prod. Casing: 5 1/2" 14# at 3111' w/100 sx.  
Perforations: 3094-96  
Top of Salt: 1250'

Plugging Program: Set bridge plug above perforations and cap with 35' cement. Mud hole. Cut off 5 1/2" casing. Place 100' cement plug at top of stub. If stub is below top of salt, place 100' cement plug at top of salt. Place 100' cement plug to straddle bottom of 8-5/8" casing. Cap with 10 sacks of cement. Notify Oil Commission at start of operations.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ralph L Gray TITLE Consulting Engineer DATE June 26, 1974  
APPROVED BY Joe D. Ramey TITLE SUPERVISOR DATE 1974  
Dist. I, Supv.  
CONDITIONS OF APPROVAL, IF ANY: