

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Water Injection Well		7. Unit Agreement Name South Caprock Queen Unit
2. Name of Operator Union Oil Company of California		8. Farm or Lease Name Tr. 54 South Caprock Queen Unit
3. Address of Operator P. O. Box 671 Midland, Texas 79702		9. Well No. 15
4. Location of Well UNIT LETTER 0 330 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 28 TOWNSHIP 14-S RANGE 31-E N.M.P.M.		10. Field and Pool, or Wildcat Caprock Queen
15. Elevation (Show whether DF, RT, GR, etc.)		12. County Chavez

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	
OTHER Squeeze hole in 5-1/2" OD casing, treat and return to injection			

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1 - Squeeze hole in 5-1/2" OD casing at 201' with 775 sx Cl "C" cement
- 2 - Drill fill out of casing from 2,880' - 2,990'.
- 3 - Acidize perms 2,960' - 2,966' with 2,000 gals 15% HCL.
- 4 - Run 2" PCID tubing, set packer and return well to water injection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>L.H. Pardue</u> L.H. Pardue	TITLE <u>Dist. Prod. Supt.</u>	DATE <u>5-17-82</u>
ORIGINAL SIGNED BY <u>JERRY SEXTON</u> DISTRICT 1 SUPERVISOR		
APPROVED BY _____	TITLE _____	DATE <u>MAY 20 1982</u>
CONDITIONS OF APPROVAL, IF ANY:		