

Form 5-231a
(FAM, 1951)

(SUBMIT IN TRIPLICATE)

Land Office **Las Cruces**

068370

UNITED STATES

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Case No.

Yates "B"

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	X
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 6, 19 59

4 Yates-Federal

Well No. 1 is located 990 ft. from (N) line and 1650 ft. from (E) line of sec. 29

NE/4 of Sec. 29

(1/4 Sec. and Sec. No.)

14S

(Twp.)

31E

(Range)

NMPM

(Meridian)

Caprock-Queen

(Field)

Chaves

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 4214 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Oral approval was given July 2, 1959 on the following plugging procedure:

Well was filled with heavy drilling mud. A 20 sack cement plug (btm of hole) was run from 2881 to 2820'. A 15 sack cement plug (base of salt) was run from 1920 to 1875'. A 5 sack cement plug (surface) was run with regulation marker. Plugged and abandoned July 3, 1959.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **MORRIS R. ANTWELL**Address **P. O. BOX 1058****HOBBS, NEW MEXICO**By **Burton Veteto**Title **Agent**