ages sont 8, t

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land (	Office	Jas	Cri	ceş
		008	370	7.
Lease	No.	ne popular		
			roth	iens

NOTICE OF INTE	ENTION TO DRILL		ςγ ••••	SUBSEQUENT	REPORT OF V	VATER SHI	UT-OFF		ļ
NOTICE OF INTE	ENTION TO CHANGE PLAN	s		SUBSEQUENT	REPORT OF S	HOOTING	OR ACIDIZING.		
NOTICE OF INTE	ENTION TO TEST WATER S	SHUT-OFF		SUBSEQUENT	REPORT OF A	LTERING	CASING		
	ENTION TO RE-DRILL OR		1 1				IG OR REPAIR.		-
	ENTION TO SHOOT OR AC ENTION TO PULL OR ALTE			·			ENT		
	ENTION TO ABANDON WEL		]	JOI I LEMENT					
	(INDICATE A	BOVE BY CHECK MA	RK NATU	JRE OF REPORT	, NOTICE, OR	OTHER DA	TA)		
/	-31- Um	tes		K	ey 14			<b>,</b> 1	9.
The same			<b>()</b>	. 11	193	1			
- 1 J S	is located	660 ft. fro	m   [	line and			w line o	f sec. 🤅	1
		7.4.0	es)	KS)	7. T		(**)		
NE/NV (1/4 Sec. a	nd Sec. No.)	14 (Twp.)	(Ran	ge)	N.M.D. (Meridi	an)			
Hndes:	ignated	Chave.	S			lew.	Mexico	***********	_
Capro	ield week	(Count	y or Sub	division)		(81	tate or Territory)	1	
he elevatio	n of the derrick flo	or above sea	level i	s 4115.4	ŧt.				
110 010 ( 4010 )									
			AILS	OF WOR					
			_						
tate names of a	nd expected depths to ob	jective sands; show ing points, and al	sizes, we ll other	eights, and len important pro	gths of propo posed work)	sed casing	s; indicate mu	dding jobs,	cem
propose 200' wi	nd expected depths to observe to drill a ith 100 sack 0', set 5-1/for product	12-1/4 hes cement. 2" casing	ole WCC	to 200°	', set urs. Or	and o	cement :	8-5/8° oximat	:е
propose 200' w	e to drill a ith 100 sack 0', set 5-1/	12-1/4 hes cement. 2" casing	ole WCC	to 200°	', set urs. Or	and o	cement :	8-5/8° oximat	:е
propose 2001 wi of 290	e to drill a ith 100 sack 0', set 5-1/	12-1/4 hes cement. 2" casing	ole WCC	to 200°	', set urs. Or	and o	cement :	8-5/8° oximat	:е
propose 2001 wi	e to drill a ith 100 sack 0', set 5-1/	12-1/4 hes cement. 2" casing	ole WCC	to 200°	', set urs. Or	and o	cement :	8-5/8° oximat	:е
propose 2001 wi	e to drill a ith 100 sack 0', set 5-1/	12-1/4 hes cement. 2" casing	ole WCC	to 200°	', set urs. Or	and o	cement :	8-5/8° oximat	:е
propose 200' w	e to drill a ith 100 sack 0', set 5-1/	12-1/4 hes cement. 2" casing	ole WCC	to 200°	', set urs. Or	and o	cement :	8-5/8° oximat	:е
propose 200' w	e to drill a ith 100 sack 0', set 5-1/	12-1/4 hes cement. 2" casing	ole WCC	to 200°	', set urs. Or	and o	cement :	8-5/8° oximat	:е
propose 2001 w of 2900 e Jueen	e to drill a ith 100 sack 0', set 5-1/	12-1/4 hes cement. 2" casing ion.	ole WCC and	to 200° 24 hou cement	, set urs. Or t with	and (	cement to appresacks to	8-5/9° oximat o test	:e
propose 200' wi of 290e e Jueen	e to drill a ith 100 sack 0', set 5-1/ for product	12-1/4 hes cement. 2" casing ion.	ole WCC and	to 200° 24 hou cement	, set urs. Or t with	and (	cement to appresacks to	8-5/9° oximat o test	:e
propose 2001 will of 2800 e Queen	e to drill a ith 100 sack o', set 5-1/for product	12-1/4 he s cement. 2" casing ion.  ust receive approval	ole WCC and	to 200° 24 hou cement	, set urs. Or t with	and (	cement to appresacks to	8-5/9° oximat o test	:e
propose 2001 wi of 2800 e Queen	e to drill a ith 100 sack o', set 5-1/ for product	12-1/4 he s cement. 2" casing ion.  ust receive approval ANTWEIL 1058	ole WCC and	to 200° 24 hou cement	, set urs. Or t with	and or ill 125 or	cement to appresacks to	8-5/9° oximat o test	:e