(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Land Office		
	ن صرب	60370
Lease No		·
Unit		1 1 1
可能 ()为		

100 KM 11 M 7:53

NOTICE OF IN	TENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF IN	TENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF IN	TENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF IN	TENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF IN	TENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF IN	TENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
OTICE OF IN	TENTION TO ABANDON WELL	
	(INDICATE ABOVE BY CHECK MA	ARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
		19 ⁵
ell No.	is located ft. fro	om. $\{ \begin{matrix} \mathbf{N} \\ \mathbf{S} \end{matrix} \}$ line and $\{ \begin{matrix} \mathbf{E} \\ \mathbf{W} \end{matrix} \}$ line of sec.
(1/ Sec.	and Sac No.) (Twn.)	(Range) (Meridian)
Dest.	(Field) (Coun	s lew lexico
	(Field) (Coun	ity or Subdivision) (State or Territory)
Wid	a second and a discount of the	₩844 × 1845 ;
e elevatio	on of the derrick floor above sea	level isft.
		•
	DET	AILS OF WORK
	and expected depths to objective sands; show ing points, and s	sizes, weights, and lengths of proposed casings; indicate mudding jobs, comer all other important proposed work)
ropose ircula et 5 1/ emplete ith ro	to drill a 12 1/4 hele casent to surface. /2, 15.504, at 31001,	
ropose irculat et 5 ly emplete ith rot	to drill a 12 1/4 hole to drill a 12 1/4 hole cament to surface. /2, 15.500, at 3100', in open and in open to be well and to be well and the surface.	raizes, weights, and lengths of proposed casings; indicate mudding jobs, cemerall other important proposed work) Leto 310'. Let 9' (1, 40%, at 310'. Fill 7 7/5 hole to approximately 31 (2556 to 150') acts. Drill out and the below 5 1/2. Well to be drill (160%) as \$200 10'. Company as \$200 10'. ANTERIL-YATES-FEED and the commenced of the commenced of the commenced of the commenced.
ropose irculation et 5 1, caple to ith rot ith rot ompany	and expected depths to objective sands; show ing points, and set of surface. 10 Smill a 12 1/4 holde cament to surface. 10 John and in operating the test of the surface. 10 John and in operating the test of the surface. 11 John and to be surface. 12 In John and in operating the surface of the surface.	raizes, weights, and lengths of proposed casings; indicate mudding jobs, cemerall other important proposed work) Leto 310'. Let 9' (1, 40%, at 310'. Fill 7 7/5 hole to approximately 31 (2556 to 150') acts. Drill out and the below 5 1/2. Well to be drill (160%) as \$200 10'. Company as \$200 10'. ANTERIL-YATES-FEED and the commenced of the commenced of the commenced of the commenced.