ra. S	<b>5</b>	ı	

## (SUBMIT IN TRIPLICATE)

Land Office	LC	
Longo No		
	0	

Ост

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO THET WATER SHIT-OFF	SUBSEQUENT REPORT OF ALTERNIC CASING.
HOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO PULL OR ALTER CASING	
Notice of Intention to Convert Ne	It to water Injection Service X
(IMBICATE ABOVE BY CHECK MAI	
	September 26
South Caprock Queen Unit Tract 7A Vell No. 15-35 is located 990 ft. fro	om. S line and 1980 ft. from E line of sec. 33
SEL Sec. 33 14-S (V. Rec. and Rec. No.) (Twp.) Caprock Queen Chaves (Field) (Count	
(% fee, and fee, No.) (Tup.)	(Renge) (Manufacture) New Mexico
Caprock Queen Chaves (County)	New Mex (CO  ky or Bubdivision) (State or Turritory)
resent Condition of Well TD= 3128'	r sines, weights, and longthe of proposed easings; indicate mudding jobs, come all other important proposed work)
ETD = 3128' 5½C 3128', perfs. 3110' - 3116' Well on production	•
5½C 3128*, perfs. 3110* - 3116* Well on production  roposed Work Pull rods, pump and tubing. Clean out to ETD of 3128*. Run 2" plastic lined tubing with water injection.	th tension packer on bottom. Place well on ve Order WFX-152 dated 9-23-63.
5½C 3128*, perfs. 3110* - 3116* Well on production  roposed Work  Pull rods, pump and tubing. Clean out to ETD of 3128*.  Run 2" plastic lined tubing with water injection.  Authority: NMOCC Administrative species	th tension packer on bottom. Place well on ve Order WFX-152 dated 9-23-63.
5½C 3128*, perfs. 3110* - 3116* Well on production  roposed Work  Pull rods, pump and tubing. Clean out to ETD of 3128*.  Run 2" plastic lined tubing with water injection.  Authority: NMOCC Administrative spreads	th tension packer on bottom. Place well on ve Order WFX-152 dated 9-23-63.
5½C 3128*, perfs. 3110* - 3116* Well on production  roposed Work  Pull rods, pump and tubing. Clean out to ETD of 3128*.  Run 2" plastic lined tubing with water injection.  Authority: NMOCC Administration	th tension packer on bottom. Place well on ve Order WFX-152 dated 9-23-63.