


(SUBMIT IN TRIPLICATE)

Land Office **Las Cruces**  
Lease No. **66370**  
Unit **Yates Bros.**

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 27, 1955

Well No. **4-Yates** is located **990** ft. from **XXX** line and **545** ft. from **E** line of sec. **33**  
**SE/4 SE/4 of Sec. 33** **14S** **31E** **N.M.P.M.**  
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
**Drickey** **Chaves** **New Mexico**  
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drill 12" hole, set and cement 310 of 8-5/8. Circulate cement to surface, drill a 7-7/8 hole to approximately 3100, set and cement 5" with 100 sacks cement. Test the Queen for production.

Note: This location staked 545'fel due to topographical conditions.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **WILLIS E. ANTHELL, Oil Operator**

Address **Box 1058, Hobbs, N.M.**

By **Ken Jennings**  
Title **Agent**