

OF COPIES RECEIVED	
DISTRIBUTION	
DATE	
FILE	
S.G.S.	
AND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
Eastcap Queen	
8. Farm or Lease Name	
9. Well No.	
26	
10. Field and Pool, or Wildcat	
Caprock Queen	
12. County	
Chaves	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input type="checkbox"/>	GAS WELL <input type="checkbox"/>	OTHER- <u>Water Injection</u>
2. Name of Operator		
Miller & Miller Auctioneers, Inc.		
3. Address of Operator		
4. Location of Well		
UNIT LETTER <u>F</u> , <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM		
THE <u>West</u> LINE, SECTION <u>34</u> TOWNSHIP <u>14 South</u> RANGE <u>31 East</u> NMPM.		

15. Elevation (Show whether DF, RT, GR, etc.)
---

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>
	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plugging Program: Set bridge plug above perforations and cap with 35' cement. Mud hole. Cut off 5 1/2" casing. Place 100' cement plug at top of stub. It stub is below top of salt, place 100' cement plug at top of salt. Place 100' cement plug to straddle bottom of 8 5/8" casing. Cap with 10 sacks of cement. Notify Oil Commission at start of operations.  
→ 24 hrs before setting bottom plug.

All cement plugs must be spotted through tubing.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>B. J. S. S. S.</u>	TITLE <u>Vice President</u>	DATE <u>10-14-74</u>
APPROVED BY <u>John W. Rungt</u>	TITLE <u>Geologist</u>	DATE <u>10-15-1974</u>
CONDITIONS OF APPROVAL, IF ANY:		