

NEW MEXICO OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

RECEIVED

OCT - 6 1950

OIL CONSERVATION COMMISSION
HOBBBS OFFICE

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	X
NOTICE OF INTENTION TO DEEPEN WELL			

Monument, New Mexico

October 4, 1950

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico

Gentlemen:

Following is a notice of intention to do certain work as described below at the.....

Amerada Petroleum Corporation

State R "A"

Well No. **1** in **C/SW/4 SW/4**

Company or Operator

Lease

of Sec. **22**, T. **8-S**, R. **12-E**, N. M. P. M., **Wildest** Field.
Chaves County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

11621' - Total Depth - Granite Wash. Finished drilling 7-7/8" hole at 4:30 A.M., 10-2-50. No oil or gas zones of consequence were encountered. It is our intention to plug & abandon this well, after running Schlumberger's Electrical, Gamma Ray & Microlog Surveys. We propose to plug the well as follows: Run drill pipe open-ended & spot 35 sacks cement at 11621', with drill pipe at 11018' spot 35 sacks cement, pull drill pipe to 4950' & spot 35 sacks cement, pull drill pipe to 3525' & spot 35 sacks cement. Jet off 8-5/8" casing at approximately 435' and recover same. Pull drill pipe to 360' & spot 50 sacks cement. Place 10 sacks cement in top of 13-3/8" surface casing and set a piece of 4" Line Pipe, as marker, in top of surface casing, extending four (4) feet above ground level. Heavy mud between all of the above cement plugs.

Approved.....
except at follows:

OCT - 6 1950

19.....

Amerada Petroleum Corporation

Company or Operator

By *Don T. [Signature]*

Position **Assistant District Superintendent**
Send communications regarding well to

Name **Amerada Petroleum Corporation**

Address **Drawer D, Monument, New Mexico**

OIL CONSERVATION COMMISSION,

By *[Signature]*
Title **Engineer District 1**