

COUNTY	CHAVES	FIELD	Chaveron	STATE	NM	CWWC
OPR	HUMBLE OIL & REFG. CO.				MAP	
5 New Mexico State "BX"						
Sec. 16, T-8-S, R-33-E				CO-ORD		
665' FSL, 662' FWL of Sec.						
Re-Spd 5-23-66		CLASS		EL		
Re-Cmp 7-4-66		FORMATION	DATUM	FORMATION	DATUM	
CSG & SX - TUBING						
8 5/8" 319' 250						
4 1/2" 4424' 300						
LOGS EL GR RA IND HC A						
		TD 4425', PBD 4302'				
IP San Andres Perfs 4231-4279' Pmpd 16 BOPD + 45 BW. Pot. Based on 24 hr test.						

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. PROP DEPTH 4400' TYPE WC
DATE

F.R. 5-26-66; CWWC
(Orig. The Atlantic Refg. Co., #1 Humble-State,
PSA 12-29-63, OGD 4425')
Elev. 4392' DB, Orig.

6-6-66 TD 4425', PBD 4302', swbg.
OO to 4302'
Perf 4231-79' W/1 shot every 2 feet
Acid (4231-79') 2000 gals.
Swbd 2 EO + 11 BW/9 hrs (4231-79')

6-13-66 TD 4425', PBD 4302', EO Pump.
Frac (4231-79') 40,000 gals wtr + 50.000% sd.

6-20-66 TD 4425', PBD 4302', pmpg load.
Pmpd 83 BLW, w/tr. oil in 24 hrs.

6-27-66 TD 4425', PBD 4302', pmpg load.
Pmpd 68 BLW + 15 EO/24 hrs.

7-5-66 TD 4425', PBD 4302', WO Potential.
Pmpd 16 EO + 45 BW/24 hrs.

7-11-66 TD 4425', PBD 4302', COMPLETED.

WC COUNTY Chaves FIELD Wildcat STATE N.M. NO. _____

OPR. Wilson, Max M. MAP _____

NO. 1 LSE Humble-State

SEC. 16 T. 8S BLK. 33E SUR _____ CO-ORD. _____

LOC. 665' fr S Line & 662' fr W Line of Sec.

MI. FROM P&A CLASS. _____ EL. 4392'

SPUD. 11-8-63 COMP. 12-29-63 FORMATION _____ DATUM _____ FORMATION _____ DATUM _____

TRT. _____ Sample: _____

CSG. & SX. _____ LOG: _____

8 5/8" 319' 250 Vates 2337

4 1/2" 4424' 300 SA 3530

_____ Slaughter

TBG. DEPTH _____ SIZE _____ 4254

LOGS EL GR RA IND HC A _____

_____ TD 4425' _____ PB 4359'

PROD INT. (DAILY RATE) BS&W GH GOR GTY C. P. T. P. HRS. TEST

PLUGGED & ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. _____ PROP DEPTH 4500' TYPE _____

DATE _____

F.R. 11-7-63
PD 4500' - San Andres

11-11-63 Drlg. 60'.
11-18-63 TD 61', WO Rotary.
11-26-63 TD 61', WO Rotary.
12-2-63 Drlg. 2910'.
12-9-63 Drlg. 4160'.
12-16-63 TD 4425', prep to perf.
Cored 4280-4330', rec 48' dolo., w/scatt. show
oil & PPP.
Cored 4331-70', rec 38' xlyn dolo., w/scatt. shows
bldg. oil.

12-30-63 TD 4425', PB 4359', PLUGGED & ABANDONED.
Perf 4336-4354' W/4 SPF
Ac. 2000 gals.
Swbd 18 BLO, 48 BAW & 116 B Sul. Wtr/13 hrs.
Squeezed Perfs 4336-4354' W/355 sx.

12-30-63 -cont'd-
Re-Perf 4337-52' W/4 SPF
Ac. 1000 gals,
swbd 70 B Sul. Wtr, w/SSO in 5 hrs.
Squeezed perfs 4337-52' W/30 sx.