

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPL
(Other instructions
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0174930-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Drilling Well		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR The Atlantic Refining Company		8. FARM OR LEASE NAME Mona Federal #4	
3. ADDRESS OF OPERATOR P. O. Box 1978, Roswell, New Mexico		9. WELL NO. 4	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 650' SUL & 650' SUL (Unit F)		10. FIELD AND POOL, OR WILDCAT Tobac-Pennsylvanian	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4400' DF	
		12. COUNTY OR PARISH Chaves	
		13. STATE N. M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	☐	PULL OR ALTER CASING	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETE	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☐
REPAIR WELL	☐	CHANGE PLANS	☐
(Other)	☐		☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	☒	REPAIRING WELL	☐
FRACTURE TREATMENT	☐	ALTERING CASING	☐
SHOOTING OR ACIDIZING	☐	ABANDONMENT*	☐
(Other)	☒ 8-pud		☒

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Digged up Moran Oil Prod. & Drilg. Corp. rotary rig and spudded well at 6:00 P.M. 1/23/65. A 17-1/2" hole was drilled to 402'. Set 12 jts 13-3/8" OD 8R 42# H-40 casing at 392.48' & cemented w/340 sx Incor neat cement + 2% CaCl. Cement circulated. WOC 19 hrs. Tested 13-3/8" casing to 1000' for 30 min. Held OK. Drilled 11" hole to 3562'. Set 109 jts 8-5/8" OD 8R 24# J-55 & 32# H-40 casing at 3561.40'. Cemented w/700 sx 1:1 Incor Pozmix, 8% gel, 2% CaCl, followed by 250 sx Incor neat cement. Top of cement by temperature survey 1290'. WOC 31 hrs. Tested 3-5/8" casing to 1500' for 30 min. OK.

18. I hereby certify that the foregoing is true and correct

SIGNED *W. L. Stetson*TITLE Dist. Drilling SupervisorDATE 2-10-65

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

APPROVED

FEB 15 1965

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.