

WC COUNTY CHAVES FIELD Wildcat STATE N.M.

OPR CHAMBERS & KENNEDY MAP

1 Wolf-Federal

Sec. 29, T-8-S, R-32-E

660' fr N Line & 1980' fr W Line of Sec.

Spud 12-7-64

CLASS EE 4350' ~~4350'~~

P & A 1-22-65	FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING	LOG:			
8 5/8" 371' 350	Anhy 1566			
4 1/2" 4244' 100	Yates 2104			
	SA 3306			
	SA Poro.			
	4050			
LOGS EL GR RA IND HC A				
	TD 4250', PBD 4192'			

PLUGGED & ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. PROP DEPTH 4700' TYPE
DATE

F. R. 12-10-64; Oper's Elev. 4376' KB.
PD 4700' - San Andres.

12-14-64 Drlg. 3725'.

12-21-64 TD 4250', WOO.
Cored 4065-4115', rec. 48' dolo & anhy.
W/scatt. shows.
DST 3995-4115', open 2 hrs.,
Rec. 360' drlg. mud,
1 hr. 30 min. ISIP 1605#, FP 401-379#,
1 hr. 30 min. FSIP 1226#.

1-4-65 TD 4250', PB 4244', prep to run tracer.
Perf. 4098-4102', 4147-54', 4157-61', W/2 SPF.
Ac. 3500 gals. 4147-61'.
Swbd. 69 BF W/tr. oil/6 hrs. & swbd. down.
Ac. 2000 gals. 4098-4102'.
Swbd. @ rate of 4 1/2 B Salty Sul. WPH.

1-11-65 TD 4250', PB 4192', swbg.
Sq. Perfs. 4098-4161' W/100 sx.
Re-Sq. Perfs. 4098-4161', W/100 sx.
Drld. out to 4192'.
Re-Perf 4132-39', 4142-46' W/2 SPF
Ac. 2000 gals.
Swbd. load.
Swbd. 3 BFPH (100% salty Sul. Wtr. W/tr. oil.)

1-18-65 TD 4250', PB 4192', prep to P&A.
Perf. 4084-88' W/2 SPF.
Set Pkr. @ 4117'.
Ac. 2000 gals. 4084-88'.
Swbd. load.
Swbd. 25 B Salty Sul. Wtr./3 hrs. W/NS.

1-25-65 TD 4250', PBD 4192', PLUGGED & ABANDONED.
