

NEW MEXICO STATE BW #5

662' FSL & 1997' FEL (O)

Sec 21 - T8S - R33E

Chaves Co., NM

Chaveroo Field

Elev: DF: 4390

GL: 4380

DF-GL = 10

API # 30-005-10084

395'-10 3/4" - Cmt to surf w/ 375 sx

Perf 445'

Sq 35 sx out & leave 35 sx inside 445' to 345'

Perf 1850'

Sq 35 sx out & leave 35 sx inside 1850-1750'

10' Surface Plug w/ cement

T/ Rustler 1800'

T/ Salt '

T/ Yates 2357 '

T/ Queen 3032 '

T/ San Andres-3548'

TOC-2000'

3536'- 7 5/8" cmt to surf w/ 500 sx

35 sx Cement 3550' - to -3450'

Cut 4 1/2" Casing +/- 3500'

TOC = 3600' Temp Log

35' Cement cap

CIBP @ 4150'

4247'

shot/every 2'
32 holes

4309'

PBTD 4346'

4364' - 4 1/2", 11.6# (5/66)

Cmt w/ 200 sx

Cut off 7750' +/-

8988'

8997'

9115'-4 1/2" w/ 300 sx (4/65)

TD:9115'

no pumping unit

by: CAR

09/24/01