

COUNTY	CHAVES	FIELD	Chaverco	STATE	NM	OWWO
OPR	HUMBLE OIL & REFG. CO.					MAP
5 New Mexico State "EW"						
Sec. 16, T-8-S, R-33-E						
662' FSL, 1997' FEL of Sec.						
Re-Spd 4-29-66						
Re-Cmp 5-5-66						
		CLASS		EL <i>and f</i> [REDACTED]		
		FORMATION	DATUM	FORMATION	DATUM	
LOGS & SX - TUBING						
10 3/4" 395' 375						
7 5/8" 3586' 500						
4 1/2" 9115' 300						
LOGS EL GR RA IND HC A						
		TD 9115', PBD 4346'				

IP San Andres Perfs 4247-4307' Swbd 138 EOPD + 195 BW. Pot.
Based on 8 hr test of 46 BO + 65 BW. Gravity 22.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. PROP DEPTH PE 5000' TYPE WO
DATE

4-16-66 F.R. 4-21-66; OWWO
PD 5000' - SA
(Orig. P&A 5-16-65, OTD 9115')
Elev. 4390' DF, Orig.
TD 9115', PBD 4346', COMPLETE.
Set BP @ 4346'
Perf @ 4247', 4249', 4251', 4253', 4255',
4257', 4259', 4261', 4263', 4265', 4267',
4269', 4271', 4273', 4275', 4277', 4279', 4281',
4283', 4285', 4297', 4299', 4301', 4303', 4305',
4307' W/1 SPI
Ac (4247-4307') 1000 gals.

COUNTY	CHAVES	FIELD	Tobac-Penn	STATE	N.M.
OPR	HUMBLE OIL & REFG. CO.			MAP	
	5 New Mexico State "BW"			CO-ORD	
	Sec. 16, T-8-S, R-33-E				
	662' fr S Line & 1997' fr E Line of Sec.				
	Spud 3-18-65				
	Comp. 5-16-65				
CSG & SX - TUBING	LOG	FORMATION	DATUM	FORMATION	DATUM
10 3/4" 395' 375		Bustl 1800			
7 5/8" 3586' 500		Yates 2357			
4 1/2" 9115' 300		Queen 3032			
		SA 3548			
		Glor 4944			
		Tubb 6412			
		Abc 7308			
LOGS EL GR RA IND HC A		TD 9115'			

PLUGGED & ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.
DATE

PROP DEPTH 9100' TYPE

3-22-65 F. R. 3-18-65; Oper's Elev 4390' DF.
 3-29-65 PD 9100' - Bough "C".
 4-5-65 Drlg. 3093'.
 4-12-65 Drlg. 5956'.
 4-19-65 Drlg. 7974'.
 Drlg. 8905'.
 TD 9115', FB 9088', prep to Ac.
 Perf. @ 8988', 8992', 8993', 8994', 8995',
 8996', 8997' W/1 3PI.
 LOG TOPS: W. C. 8122', Bo "C" 8978'.
 4-26-65 TD 9115', PB 9088', WOC.
 Ac. 250 gals., swbd. dry.
 Re-Ac. 3000 gals.
 Swbd. 126 BI & AW + 54 BFW/11 hrs.
 Set Ret. @ 8955'.
 Sq. 8988-97' W/75 sx.

5-3-65 TD 9115', PB 9088', swbg.
Re-Perf. @ 8992', 8995', 8997' W/1 SPI.
Re-Ac. 250 gals., swbd. 5 BL & AW/5 hrs.
Re-Ac. 1000 gals.
Swbd. 60 BL & AW + 21 BNW/5 hrs.
Swbd. 18 BO + 12 BW/8 hrs.
5-10-65 TD 9115', PB 9088', swbg.
Re-Ac. 2000 gals. 8992-97'.
Swbd. 2 BLW + 25 BNW + 2 BO/10 hrs.
Swbd. 13 BW + 3/4 BO/10 hrs., swbd. dry.
5-17-65 TD 9115', PB 9088', Completed.
Re-Ac. 3000 gals. 8992-97'.
Swbd. Load.
Swbd. 42 BFW/3 hrs. W/NS.